


1.8M ECO SOLVENT PRINTER




1. Motor: server motor driver, quality assurance, high resolution and stable.
2. Guiderail: Taiwan HIWIN silent THK, high resolution, mute.
3. Cleaning: Position-lift cleaning ink station, one-step cleaning.
4. Feed-in and Feed-out: front and back standard with feed-in and feed-out system.
5. Drying: Front and back platform heating, external with up and down dual drying system, fully meet the fast speed printing.
6. Exterior: Industrial design, stable working, left and right clamshell, convenient maintenance.
7. Transfer: Cable printing interface, one computer can be linked to multi equipments.
8. Resolution: 1440 dpi

Machine details



Automatic lifting ink stack

Automatic lifting ink stack, automatic cleaning, closed nozzle, so that the nozzle is always in good condition.



Double servo motor

Up to 12K ignition frequency, 30% increase in printing speed, belt drive stepping system, more quiet paper.



Segmented drying system

Two-stage infrared heating, can be controlled in sections, the picture is printed and dry, with automatic paper collector, unattended printing is realized.



Continuous ink supply system

Intelligent ink supply system, constant liquid level, to ensure high speed and high output of printing ink, capacity up to 2000ml.

Print effect display



Outdoor advertising



Advertising light box



Indoor advertising



KT version



Yilapao/exhibition stand




Photo paper/hanging picture



wallpaper



Car sticker



DISEN SINCE 1994,WORRY-FREE AFTER-SALES. Professional production factory,Quality assurance

Parameters and specifications



Model: DS1801

Print head: XP600/i3200

Number of printhead: 1pc

Maximum print width: 1.8m

Color: CMYK 4color

Printing resolution: 1440 dpi

Cleaning of printhead: Automatic

Heating system: Front/ Back

Drying system(Infrared): Optional

Drying system(Fan): Equipped

Auto media take-up system: Equipped

Platform suction contro: Equipped

Lifting system: Unequipped

Working environment: 15-30°C

Relative humidity: 40-60%

RIP software: Maintop

Operating system: WinXP/Win7

Voltage: AC220V50-60HZ

Power: 600W

Package size: 2900x740x670mm

Printer sizet: 2837x455x1300mm

Weight: 210±5%kg

Printer weight: 160±5%kg

Compatible ink: Eco-solventink/Water-based ink/ Sublimation Ink etc

MPrinting media: Water-based: PP/ Backlit film/ Photo?paper/ Movable self-adhesive vinyl/ Pictorial cloth

Eco-solvent: Car sticker/ Lamp cloth/ Face film/ Coated banner/ Flag cloth

Printing: Thermaltransfer paper/Pure cotton Special: Wallpaper/Canvas/ Chinese art paper/Grid cloth

Printing speed: Draft mode:20m² Production:17m² Quality mode:15m²