

A3 DTF PRINTER

Convenient, high efficiency and low cost: One-stop hollow printing, no cutting plotter, laminating machine, hollow machine, no waste discharge, time and labor saving.













Continuous ink supply system

High-precision guide rail

Control panel

Print sample display









T -shirt

coat

jeans

shoe







PARAMETERS AND SPECIFICATIONS

Printhead	EPS4720/i3200/XP600
Number of print head	1/2
Printer size	900*480*510mm
Maximum printing width	A3/330mm
Printer weight	60kg
Outer packing size	960*630*620mm
Printing software	Maitop 6.1/photoprint
language	Chinese/English
Print speed	[4720] 4Pass:10m²/h, 6Pass:6m²/h, 8Pass:4m²/h
	[i3200] 4Pass:10m²/h, 6Pass:6m²/h, 8Pass:4m²/h
	[XP600] 6Pass:4.5m²/h, 8Pass:3.5m²/h
Printing accuracy	360*2400dpi,360*3600dpi,720*2400dpi (6Passs,8Pass)
Environmental conditions	Temperature:20-28°C/Relative Humidity: 65%-75%
Ink type and configuration	Textile Pigment ink (FY/FM/FB/FR/FG/C/M/Y/K/W)
Working Power supply	220V/110V 50HZ/60HZ
The Ironing temperature	160-170°C Cold /hot to tear
Power	Printer:350w / Powder dryer:2400W
Three heating sections	Pre-heater, printing bed heater, rear heater 30°C-65°C
Powder shaker name	A3 shaking powder drying machine
Retractable media width	330MM
Applicable media	Cloth, nylon, chemical fiber, face cloth, leather, swimsuit, PVC, EVA, etc.
functional item	Powder shaking control, dusting control, curing temperature PID setting
Heating and drying function	Far infrared carbon fiber heating tube heating
Rewind function	Automatic induction winding
Electrical parameters	Rated voltage 220V, 110V, rated current 5A, rated power 800W
Dimensions and Weight	XP600: Shake powder machine Packing size: 780*610*710mm, 45KG
	i3200: powder shaker Package size: 890*740*580mm, 50KG