

Four heads DTF PRINTER

Anti-collision system protects the print head from being scratched or damaged.

Anti-collision system protects the print nead from being Aluminum allov ink stack stable lifting without shaking It has independent power supply protection and is not easy to be powered off.













Parameters and specifications

| Davameters | W | minin | W | W.die |
|---------------------|--|--------------|---------------------------|--------|
| Parameters Model | and specifications | Nozzie Model | i3200 A1 /i1600 A1 | VV-QIS |
| Number of nozzles | 4 | Print speed | 4Pass 28m²/h 6Pass 22m²/h | 1 |
| Print media | Hot Stamping Film | Ink Type | Heat transfer ink | 1 |
| Printing interface | Gigabit network interface | Media Width | 650mm | 1 |
| Power | 220V/110V 450W | Print height | Adjustable height 0-12mm | 1 |
| Ink supply system | 1.5L ink bottle + secondary ink supply + white ink circulation + stirring | | | 1 |
| Drying system | The printer has front, middle and rear heating, and the powder shaker has built-in infrared drying | | | 1 |
| Retractable system | 15 rpm high speed motor retracting and extending system | | | 1 |
| RIP Software | Monte, PP, PF | File Format | PDF, JPEG, TIFF, etc. | h- |
| Machine weight | 110KG | Machine size | 1770x810x1470mm | Prin. |
| Packing size | 1830x830x820mm | Co | | "" |