

Double head 1.8-3.2m Sublimation printer

Machine Features

1. Hansen network port board, high precision, fast speed, bright and delicate printing pictures, good stability
2. Equipped with ink shortage and paper shortage alarm function, trolley anti-collision device and emergency stop button, truly unattended
3. Industrial-grade high-precision platform to ensure the flatness of the printing surface
4. Equipped with advanced intelligent nozzle cleaning and moisturizing device, it provides safe and convenient nozzle cleaning and maintenance functions, making operation and maintenance more convenient and quick



Sample display



Parameters and specifications

| | | | |
|---------------------|--|--------------------|---|
| Model | DS-R1802S | Sprinkler type | i3200E1/A1/DX5 |
| Max printing width | 1800mm | Nozzle height | 2mm-3mm |
| Printing speed | 4 colors 8 colors | Printing height | 1.5mm-5mm Adjustable |
| | 4pass: 100m ² /h | Media weight | 75KG |
| | 6pass: 64m ² /h | Printing media | Leather, Canvas, Banner, PVC Vinyl, Photo Paper, Silk Fabric, etc |
| Inks | Inks type: Water-base/Eco solvent | | |
| | Ink Color: Four colors: C/M/Y/K Eight colors: C/M/Y/K/Lc/Lm/Lk/LIK | | |
| | Ink Supply: Dalian ink supply | | |
| Platform heating | front, middle and rear | Connecting port | USB2.0 |
| Take up system | Take up system with double automatic motors | Heating system | Infrared heating system |
| RIP Software | Maintop, Photoprint, Wasatch, ONYX | Power | 3800W |
| Working environment | Temperatue: 20°C-35°C / Humidity: 35%RH-65% | Power supply | AC110V±10%, AC220V±10%, 50/60hZ |
| Packaging size | L2855xW840xH1350mm | Box Packaging Size | L2980xW750xH730mm |
| Net weight | 160KG | Gross weight | 180KG |