

Type	Rated power kW	Rated voltage V	Rated current A	Rated speed r/min	Block current	Block torque	Pull-in torque	Max. torque	Moment of inertia $\text{tf} \cdot \text{m}^2$	Exlcting data(Rated)	
					Rated current	Rated torque	Rated torque	Rated torque		Voltge V	Current A
TKK1600-4/1430	1600	11000	98	1500	6/6.5	1.5/1.0	0.89/1.0	2/1.8	1.2	30	304
TKS2500-4/1430	2500	10000	168	1500	5/6.5	1.56/1.0	0.98/0.7	2/1.7	1.4	39	366
T800-6/1180	800	6000	90	1000	6.4/7.0	1.92/1.0	113/1.0	2.11/1.8	0.5	33.5	243
T1000-	1000	6000	112	1000	6.62/7.0	1.74/1.0	1.275/1.0	2.25/1.8	1.0	37.5	290
T1250-	1250	6000	140	1000	5.62/7.0	1.58/1.0	1.1/0.9	1.97/1.8	0.68	35.0	320
T1600-	1600	6000	178	1000	7.24/7.5	1.99/1.5	1.324/1.0	2.15/1.9	1.03	42.7	292
T1600-	1600	10000	123	1000	5.72/6.0	0.982/0.9	1.46/1.0	2.68/2.0	3.3	68	349
T3200-	3200	10000	214	1000	7.0/6.5	1.9/1.0	0.8/0.9	1.8/2.0		48	402
T800-8/1180	800	6000	91	750	5.58/6.0	1.22/1.0	1.11/0.9	2.1/2.0	0.55	31	372
T1000-	1000	6000	113	750	5.7/6.0	1.2/1.0	1.167/0.9	2.09/2.0	0.76	39.8	320
T1250-	1250	6000	141	750	5.17/6.0	1.276/1.1	0.972/0.9	2.14/1.8	1.7	46.0	349
T1600-	1600	6000	179	750	5.69/6.0	1.16/1.0	1.18/0.9	2.06/1.8	2.3	52.4	310
T2000-	2000	6000	224	750	5.5/6.0	1.29/1.0	1.06/0.9	2.0/1.8	2.0	70.5	283
T2500-	2500	10000	169	750	7.39/7.5	1.329/1.0	1.649/1.0	2.27/2.0	5.4	89.0	308
T3200-	3200	6000	356	750	6.37/6.5	1.445/1.0	1.25/1.0	2.14/1.8	5.8	74.9	350
T8000-	8000	10500	568	750	7.39/7.5	1.39/1.0	1.88/1.3	2.63/2.0	2.1	94.5	440
T630-	630	6000	72	600	5.19/6.5	1.16/1.0	1.26/1.0	2.06/1.8	0.7	50.0	225
T630-	630	10000	43	600	6.06/6.5	1.52/1.0	0.95/0.9	2.24/2.0	0.91	57.3	177.7
T800-	800	6000	91	600	6.35/7.0	1.26/1.1	1.37/1.1	2.1/2.0	0.8	60.0	231
T800-	800	6000	93	600	6/6.5	2/1.0	1.0/0.9	2/2		40.0	278
T1000-10/1430	1000	6000	113	600	5.83/6.0	1.8/1.2	1.01/0.9	2.15/2.0	1.8	46.7	264
T1600-10/1430	1600	6000	177	600	6.65/7.0	2.0/1.5	1.16/1.0	2.23/2.0	2.9	54.2	364
T2500-10/1730	2500	6000	279	600	6.42/6.5	1.01/0.8	1.55/1.1	2.14/2.0	5.0	82.0	297

T3200-10/1730	3200	10000	214	600	5.11/6.0	0.7/0.6	1.305/1.0	1.99/1.8	4.89	71.1	370.4
TK560-12/1180	560	10000	38	500	6.0/6.5	2.0/1.0	1.1/0.9	24/20	0.7	55	148
TK710-12/1180	710	10000	48	500	6.0/6.5	1.9/1.0	1.0/0.9	24/20	0.8	70	160
T400-	400	6000	46	500	6.13/6.5	1.4/1.0	1.18/1.0	2.37/2.0	0.61	53.0	158
T500-	500	6000	58	500	5.15/6.0	1.01/0.8	1.094/0.9	2.005/1.8	0.67	58.0	163
T630-	630	6000	72	500	5.38/6.0	1.06/0.8	1.09/0.9	2.27/2.0	1.1	44.4	253
T800-	800	6000	90	500	5.16/6.0	1.02/0.8	1.05/0.9	2.16/2.0	1.7	57.7	254
T1000-12/1430	1000	6000	113	500	5.53/6.0	1.04/0.9	1.17/0.9	2.18/2.0	1.7	55.4	258
TK1000-12/1430	1000	10000	67.5	500	5.4/6.5	1.8/1.0	0.95/0.9	2.3/2.0	1.8	64	227
T1250-12/1730	1250	6000	141	500	5.58/6.0	1.28/1.0	1.07/0.9	2.27/2.0	4.4	62.	266
T1600-12/1730	1600	6000	179	500	5.3/6.C	1.85/1.0	1.035/0.9	2.12/2.0	4.4	68.9	245
T2500-12/2150	2500	6000	282	500	6.8/7.0	1.6/1.0	1.3/1.0	2.29/2.0	11.5	86.0	349
T3200-16/1730	3200	6000	360	500	6.39/7.0	1.52/1.0	1.23/1.0	2.13/2.0	12.0	95.4	364
T1250-16/1730	1250	6000	142	375	6.06/6.3	1.0/0.8	1.35/1.0	2.35/2.0	4.46	78.9	226.4
T1600-20/2150	1600	6000	182	300	4.52/5.0	0.833/0.75	1.032/0.9	2.07/2.0	10.8	89.0	236
T500-	500	6000	58	250	5.78/6.0	1.22/1.0	1.05/0.8	2.48/2.0	5.2	70.6	242
T1250-24/2150	1250	6000	143	250	5.2/6.0	1.064/0.5	1.046/0.9	2.19/2.0	11.0	78.0	260