

Type	Rated power kW	Rated voltage V	Rated current A	Rated speed r/min	Starting torque	Pull-in torque	Max.torque	Block current	Weight kg
					Rated torque	Rated torque	Rated torque	Rated current	
TDMK280-32/3150	280	10000	40.5	187.5	2.16	1.26	4.1	7.0	10500
TDMK320-32/2150	320	6000	37.6	187.5	2	1.1	2	6.5	10750
TDMK350-32/2150	350	6000	41	187.5	2.04	1.1	3.56	6.72	10750
TDMK400-32/2150	400	6000	47	187.5	2.115	1.32	4.06	6.542	11370
TDMK400-32/2150	400	10000	28	187.5	1.9	1.00	3.213	6.67	12170
TDMK400-32/2150	400	6000	47	187.5	1.42	0.96	3.35	5.86	11300
TDMK500-32/2150	500	6000	58	187.5	1.88	1.0	2.93	6.1	10960
TDMK500-36/2600	500	6000	58	167	2.03	1.07	3.1	6.67	13400
TDMK500-32/2150	500	10000	35	187.5	1.71	1.03	3.5	6.24	12170
TDMK500-40/2600	500	10000	35	150	1.74	1.13	3.9	6.87	16360
TDMK570-36/2900	570	6000	67	167	2	1.08	3.09	6.67	15880
TDMK600-24/2150	600	6000	69	250	1.74	1.0	2.93	5.87	10600
TDMK630-36/2600	630	6000	74	167	1.73	1.02	2.9	6.13	13500
TDMK800-36/2600	800	6000	93	167	1.7		2.7	5.9	16000
TDMK800-32/2600	800	6000	93	187.5	1.73		2.78	5.75	15800
TM800-48/3250	800	6000	92	125	1.83	1.016	4.024	6.34	29300
TDMK800-36/2600	800	10000	55	167	1.8	1.0	2.5		15500
TDMK900-36/2600	900	6000	103	167	1.77	1.01	2.98	6.14	15660

TDMK1000-36/2600	1000	6000	114	167	0.69	1.65	2.11	3.36	15100
TDMK1000-36/2600	1000	10000	69	167			2.6		17750
TDMK1250-40/3250	1250	6000	143	150	1.7	1.01	3.36	6.17	29800
TDMK1600-40/3250	1600	10000	111	150	0.6	0.6	2		27000
TDMK1600-36/3250	1600	6000	181	167	1.87	1.19	2.98	6.7	31000
TDMK1800-32/2600	1800	6000	203	200	0.873	0.891	2.13	4.37	18500
TM2000-60/4250	2000	6000	228.7	100	1.216	1.081	2.992	6.231	42200

manager@chinasi mo . com