

Type	Rated power kW	Rated voltage V	Rated current A	Rated speed r/min	Power factor ϕ	Efficiency %	Block current	Block torque	Pull-in torque	Max.torque	Flywheel torque kN m ²	Weight kg
							Rated current	Rated torque	Rated torque	Rated torque		
TK250-10/990	250	6000	29	600	0.9	92.5	4.54	1.37	0.773	2.10	2	2.5
TK250-10/1180	250	6000	29.1	600	0.9	92	5.08	0.988	1.01	2.42	3.5	4.3
TK250-12/1180	250	380	456	500	0.9	92C	3.64	0.801	0.697	2.12	2.7	2.59
TK250-12/1180	250	6000	20	500	0.9	92	4.82	1.76	0.89	2.20	5.0	4.9
TK320-12/1180	320	6000	36.8	500	0.9	92.4	5.73	1.20	1.15	2.46	4.0	4.53
TK320-12/1180	320	6000	36.8	500	0.9	93.4	5.73	1.20	1.15	2.46	4.0	3.42
TK320-12/1430	320	10000	22.6	500	0.9	91.3	5.79	1.57	1.06	2.69	8.0	4.28
TK550-12/1430	550	6000	62.9	500	0.9	93.9	4.67	1.03	0.898	2.3.5	4.9	4.16
TK200-14/1180	200	380	371	428	0.9	91.2	3.92	1.02	0.688	2.04	4.9	2.62
TK250-14/1180	250	380	454	428	0.9	92	4.23	1.14	0.729	2.10	4.9	3.12
TK250-14/1180	250	6000	29	428	0.9	91.6	4.60	1.64	0.769	2.47	5.2	3.0
TK250-14/1180	250	10000	17.6	428	0.9	91.1	5.98	1.44	1.07	2.70	6.0	3.71
TK280-14/1180	280	380	525	428	0.9	93.4	4.17	1.44	0.728	2.11	6.0	3.10
TK280-14/1180	280	6000	32.7	428	0.9	91.9	4.58	1.57	0.77	2.69	17	3.27
TK320-14/1430	320	6000	37.0	428	0.9	92.1	4.87	1.06	0.950	2.17	5.0	4.66
TK350-14/1180	350	3000	80.5	428	0.9	93.2	4.45	1.03	0.830	2.43	6.0	5.09
TK350-14/1180	350	6000	41.1	428	0.9	93.1	4.13	1.46	0.703	2.20	9.8	3.40
TK250-14/1430	350	10000	247	428	0.9	91.4	4.33	1.06	0.770	2.31	25	4.60

TK500-14/1730	500	6000	57.1	428	0.9	93.0	4.80	1.27	0.889	2.4】	13	5.37
TK550-14/1430	550	6000	63.0	428	0.9	94	5.46	1.42	1.05	2.23	24	4.92
TK550-14/1430	550	10000	38.4	428	0.9	94			0.86	2.17	1.4	5.45
TK550-14/1730	550	6000	63.0	428	0.9	93.6	5.23	1.46	0.972	2.29	35	4.89
TK630-14/1730	630	6000	72.0	428	0.9	93.9	5.17	0.842	1.16	2.29	20	8.51
TK1000-14/1730	1000	6000	113	428	0.9	94.9	4.84	1.23	0.932	2.22	60	9.66
TK220-16/1430	220	6000	25.8	375	0.9	90.3	6.22	1.3.5	1.14	3.04	50	3.20
TK250-16/1180	250	380	456	375	0.9	92.8	4.88	1.97	0.806	2.67	50	3.21
TK250-16/1430	250	6000	29.4	375	0.9	91.5	5.59	1.28	0.997	2.35	10	3.63
TK250-16/1430	250	10000	17.6	375	0.9	91.0	5.69	2.12	0.904	2.97	50	4.71
TK450-16/1430	450	6000	52.0	375	0.9	93.9	5.12	1.03	1.03	2.36	13	8.46
TK500-16/1430	500	6000	57.0	375	0.9	93.5	5.08	0.993	1.05	2.33	34	7.15
TK500-16/1730	500	6000	57.0	375	0.9	93.7	4.90	1.21	0.892	2.39	30.0	6.63
TK550-16/1730	550	6000	63.2	375	0.9	93.8	4.91	1.34	0.862	2.26	30.0	9.56
TK630-16/1730	630	6000	73.0	375	0.9	93.9	4.56	1.14	0.844	2.03	32.0	6.40
TK630-16/1730	630	6000	72.0	375	0.9	94.1	5.63	0.989	1.18	2.32	55.0	11.8
TK630-16/1730	630	10000	43.5	375	0.9	93.1	6.56	1.69	1.19	2.64		7.20
TK800-16/1730	800	6000	91.0	375	0.9	94.2	5.32	0.907	1.21	2.06	30.0	10.3
TK1000-16/2150	1000	6000	116	375	0.9	94.4	5.32	1.66	0.989	2.12	70.0	13.0
TK1000-16/1730	1000	6000	115	375	0.9	94.2	5.63	1.39	1.05	2.50	30.0	12.2
TK1250-16/2150	1250	6000	141	375	0.9	95.0	4.69	1.19	0.870	2.15	49.0	16.1
TK1250-16/2150	125(10000	85.0	375	0.9	94.6	5.88	1.06	1.27	2.14	80.0	17.3

TK1500-16/2150	1500	6000	169	375	09	95.3	5.37	0.920	121	2.14	78.0	16.6
TK1800-16/2150	1800	6000	203	375	0.9	95.5	5.67	1.09	1.25	1.91	86.0	14.0
TK300-18/1430	300	6000	34	333	0.9	92.5	6.21	1.35	1.17	2.90	35.0	8.56
TK355-18/1430	355	6000	41.0	333	0.9	92.7	6.43	1.45	1.22	2.48	10.0	6.58
TK355-18/1430	355	10000	25.0	333	0.9	91.4	4.24	1.45	0.687	2.44	10.0	7.15
TK400-18/2150	400	6000	46.5	333	0.9	93.0	6.23	1.36	0.970	2.57	55.0	11.1
TK500-18/2150	500	6000	58.0	333	0.9	93.2	4.64	0.964	0.875	2.04	45.0	11.9
TK550-18/1730	550	6000	62.9	333	0.9	93.8	4.64	1.48	0.792	2.45	29.4	5.94
TK710-18/1730	710	6000	80.3	333	0.9	94.0	4.66	1.43	0.790	2.40	35.0	6.53
TK300-18/1730	800	6000	90.0	333	0.9	94.5	4.50	0.890	0.910	2.27	35.0	7.00
TK800-18/2150	800	6000	92.0	333	0.9	94.3	5.19	1.10	1.01	2.05	74.5	12.2
TK800-18/2150	800	6000	91.9	333	0.9	94.3	4.80	0.917	0.960	2.23	53.0	10.7
TK800-18/1730	800	10000	54.9	333	0.9	93.7	5.33	1.01	1.10	2.42	40.0	7.80
TK1000-18/2150	1000	6000	115	333	0.9	94.5	5.48	1.66	0.992	2.15	81.0	13.3
TK1250-18/2150	1250	6000	141	333	0.9	94.7	4.59	1.35	0.791	2.07	92.0	16.1
TK1800-18/2150	1800	6000	202	333	0.9	95.1	5.30	0.960	1.17	2.11	100	17.3
TK2500-18/2600	2500	6000	280	333	0.9	95.6	5.86	1.56	1.06	2.21	200	25.2
TKSSSS-18/2600		6000	11	333	0.9	95	5.72	1.34	0.0元	2.12	20	28.3
TK350-20/2150	350	6000	41.1	300	0.9	92.2	5.05	1.34	0.887	2.53	55.0	11.2
TK400-20/1730	400	6000	46.0	300	0.9	93.1	6.14	1.93	1.04	3.00	50.0	11.9
TK550-20/2150	550	6000	63.0	300	0.9	93.3	4.79	1.25	0.837	2.32	60.0	12.0
TK550-20/2150	550	10000	39.0	300	0.9	93.0	4.26	1.08	0.740	2.46	49.0	11.7

TK630-20/2150	630	6000	73.0	300	0.9	93.7	5.59	1.01	1.17	2.29	55.0	11.0
TK630-20/2150	630	6000	73.0	300	0.9	93.7	5.45	1.01	1.10	2.35	84.0	11.
TK630-20/1730	630	6000	71.6	300	0.9	94.3	5.18	0.864	1.09	2.30	35.0	6.90
TK630-20/2150	630	10000	44.0	300	0.9	93.	6.19	1.57	1.10	2.77	54.0	11.8
TK650-20/2150	650	6000	75.5	300	0.9	93.9	5.21	0.948	1.07	2.27	74.0	11.9
TK800-20/2150	800	6000	92.0	300	0.9	94.0	6.5	0.600	0.600	1.80	74.0	11.0
TK800-20/2150	800	10000	55.2	300	0.9	93.7	5.01	1.49	0.870	2.40	54.0	12.7
TK1800-20/215	1800	6000	201	300	0.9	95.6	4.94	1.21	0.917	2.32	116	17.3
TK2500-20/260	2500	6000	208	300	0.9	96.0	4.57	0.763	1.05	2.03	180	27.0
TK4360-20/2600	4360	6000	483	300	0.9	96.8	5.10	1.33	0.907	2.07	356	33.0
TK1850-16/2150	1850	6000	208	375	0.9	95.5	5.6	0.97	1.27	2.1	8.0	17.2
TK2800-16/2150	2800	6000	312	375	0.9	94.5	4.92	1.29	0.89	1.93	15	22.4
TK2800-16/2600	2800	10000	188	375	0.9	95.9	3.6	0.78	0.7	1.85		22.4
TK1000-18/1730	100	6000	113	333	0.9	94.5	4.86	0.95	0.9	2.2	39	11
TK2800-18/2600	2800	10000	188	333	0.9	95.9	4.3	0.89	0.9	1.86	15	26
TK4900-18/2600	4900	6000	543	333	0.9	96.7	3.98	0.76	0.82	1.85	304	32
TK5000-18/2600	5000	6000	554	333	0.9	96.7	3.9	0.75	0.81	1.84	304	32
TK5200-18/2600	5200	10000	348	333	0.9	96.4	4.4	0.84	0.94	1.9	25	34
TK2800-20/2150	2800	6000	312	300	0.9	96	5.2	1.24		2.25	137	24.6
TK2900-20/2600	2900	6000	325	300	0.9	95.8	4.7	1.1	0.8	2	441	33
TK3800-20/2600	3800	6000	423	300	0.9	96.2	5.2	1		2	313	31.2
TK3800-20/2600	3800	10000	254	300	0.9	96.2	4.4	0.9	0.88	1.95	298	30.4

TK4800-20/3250	4800	6000	532	300	0.9	96.2	4.3	0.6	0.98	1.8	539	41
TK4000-22/3250	4000	10000	269	273	0.9	95.7	5.3	1.35	0.98	2.12	627	43.9
TK4800-22/3250	4800	10000	321	273	0.9	95.5	5.4	1.1	1.1	2	588	41
TK2500-24/2900	2500	6000	280	250	0.9	95.6	4.8	0.99	0.98	2.15	372	27
TK2500-24/2900	2500	10000	168	250	0.9	95.5	5.5	1.1	1.1	2.25	392	27

manager@chinasi mo . com