

Type	Rated Power kW	Rated Current A	Speed rpm	Efficiency %	Power Factor ϕ	Max /Rated Torque	Locked /Rated Torque	Locked /Rated Current	J(load) kg m ³	Weight kg	Lubrication Time h
Y2-4001-4	355	634.2	1490	94.5	0.90	1.8	0.8	6.5	120	2605	2000
Y2-4002-4	400	713.8		94.6					133	2740	
Y2-4003-4	450	802.1		94.7					147	2920	
Y2-4501-4	500	880.6	1490	94.8	0.91				161	2895	
Y2-4502-4	560	985.2		94.9					178	3140	
Y2-4001-6	280	509.4	990	94.3	0.88				262	2410	
Y2-4002-6	315	572.4		94.4				291	2550		
Y2-4003-6	355	644.5		94.5				325	2680		
Y2-4004-6	400	725.4		94.6				361	2880		
Y2-4501-6	450	811.2	990	94.7	0.89			401	3095		
Y2-4502-6	500	900.4		94.8				441	3365		
Y2-4503-6	560	1007.4		94.9				487	3490		
Y2-4001-8	220	433.6	745	94.0	0.82	1.8	0.8	5.5	424	2350	3000
Y2-4002-8	250	492.2		94.1					477	2490	
Y2-4003-8	280	550.7		94.2					529	2620	
Y2-4004-8	315	618.9		94.3					589	2780	
Y2-4501-8	355	672.9	745	94.3	0.84				657	2945	
Y2-4502-8	400	757.4		94.4					732	3075	
Y2-4503-8	450	851.2		94.5				814	3205		
Y2-4504-8	500	944.7		94.6				895	3415		
Y2-4001-10	160	324.6	595	93.6				544	2480		
Y2-4002-10	185	375.0		93.7				622	2680		

Y2-4003-10	200	404.9		93.8					669	2850	
Y2-4501-10	220	445.0	595	93.9	0.80				730	2995	4000
Y2-4502-10	250	505.1		94.0					822	3100	
Y2-4503-10	280	565.1		94.1					912	3215	
Y2-4504-10	315	635.1		94.2					1016	3375	

manager@chinasi mo . com