

4U Rackmount PC

SIN-610L-BH31CMA



Main feature

Intel®H310C
chipset

Intel 6th/7th/8th/9th
generation CPU

Supports up to
32G memory

VGA+HDMI+
DVI+EDP

2*Intel Gigabit
Ethernet ports

9*USB ports
(4*USB3.0)

6*COM ports
(2 RS232/485)

3*PCIe slots
4*PCI slots

	Specific parameters
Chipset	Intel® H310C chipset
CPU	LGA1151 architecture, supports Intel 6/7/8//9 generation i3/i5/i7CPU
Memory	2*DDR4 U-DIMM memory slot, 2400 MHz, maximum support 32G
Display	1*VGA interface, 1*HDMI interface, 1*DVI interface, 1*EDP connector
Hard Disk	4*SATAII interfaces, 1*MSATA interface
Network	1*Intel® i225-V Gigabit network port, 1*Inte® i219-LM Gigabit network port
Expansion	1*PCIeX16 slot, 1*PCIeX4 slot, 1*PCIeX1 slot 4*PC1 slots, 2*Mini-PCIe slots (support WIFI+4G/3G), 1*SIM card slot
COM	6*COM ports (2*support RS232/485)
USB	4*USB3.0 (Rear I/O), 2*USB2.0 (Rear I/O), 3*USB2.0 (Header)
I/O front panel interface	2*front USB2.0 ports, 1*power button, 1*reset button, 2*indicator lights, 3*optical drive slots
I/O rear panel interface	1*PS/2 port, 3*USB2.0 ports, 4*USB3.0 ports, 1*VGA port, 1*HDMI port1*DVI-D port, 6*COM ports, 2*Gigabit Ethernet ports, 1*Line-in port, 1*Line-out port, 1*MIC port, 1*LPT port, 1*power switch, 1*AC IN
Audio	Line-Out, Line-in, MIC
Power	300W power supply (replaceable 550W power supply)
Case size	430 (with ears 482) *481*177mm (width*depth*height)
Weight	About 23kg
Supported system	Windows 7/8/10, Server 2008/2012, Linux

