

Embedded fanless industrial computer

UTX-3117



### Main feature

Intel E3940/  
Intel N3350/  
Intel N4200

Support  
8G Memory

DP+HDMI

-20~60 wide  
temperature range

2\*  
Gigabit Ethernet

2\*USB3.0

2\*COM ports

2\*Min PCIe  
1\*M.2

| Specific parameters |                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------|
| Chipset             | Intel Apollo Lake E3900 Series SoC                                                                                      |
| CPU                 | Intel Atom E3940/Intel Celeron N3350/Intel Pentium N4200                                                                |
| Memory              | 2x204-pin DDR3LSO-DIMM Memory slot, supports 8G                                                                         |
| Display             | 1*DP port , 1*HDMI port                                                                                                 |
| Harddisk            | —                                                                                                                       |
| Network             | 1*Intel 1210AT Gigabit Ethernet , 1*Realtek Gigabit Ethernet                                                            |
| Expand              | 1*full-length mini-PCIe slot, 1*half-length mini-PCIe slot, 1*M.2 slot                                                  |
| COM                 | 1*RS422/485 COM port , 1*RS232COM                                                                                       |
| USB                 | 2*USB3.0 ports                                                                                                          |
| I/O front panel     | 1*DP port, 1*HDMI port, 2*USB 3.0 ports, 1*Intel Gigabit network port, 1*Realtek Gigabit network port, 1 * power button |
| I/O Side panel      | 1*RS422/485 COM port, 1*RS232 COM port, 1*audio input port, 1*power input port                                          |
| Audio               | —                                                                                                                       |
| Sound Card          | —                                                                                                                       |
| Power               | 12-24V DC in                                                                                                            |
| Size                | 128(L)x152 (W)x37 mm(H)                                                                                                 |
| Weight              | About 1.2Kg                                                                                                             |
| Installation mode   | Wall mount, DIN rail, VESA mount                                                                                        |

### 3\*DVD Optical drive

