

CE **ISO** **24h**

Easy Lift, Easy Life!

2000/2500 KGS LOAD CAPACITY
4400/5500 LBS LOAD CAPACITY

Weigh and Move Pallet Loads in Sanitary or Wet Environments.
The stainless steel pallet truck with scale allows you to weigh your load on the spot for maximum efficiency.

- 100% stainless Grade 304.
- Ideal for applications in food and medical industry.
- Small and compact electronics specially developed for mobile weighing.
- With high quality AC type pump.
- Accuracy 0.1% of the weight applied to the scale.
- Graduation 0.5kg/1lbs.
- 3"(75MM) lowered fork height available.

Warranty
3 years on pump jack or full pump jack replacement.
1 Year other parts and labour On-site warranty.

SHANGHAI SINOLIFT MECHANICAL AND ELECTRICAL EQUIPMENT CO.,LTD

ADDRESS: No. 2471 Dachuan Road, Nanhui Industry Park, Pudong New District, Shanghai, 201399,P.R.China

Tel: 0086-21-68014500 or 0086-21-58003681

Fax: 0086-21-68014262

Website: www.sinolift.com www.sinoliftchina.com

Skype: sinolift

Whatsapp & Mobile: 0086 138 1757 2420

HL-S Hand Pallet Jack Scale

Stainless Steel Hand Pallet Truck with Scale

The ideal pallet truck to handle loads in humid and damp conditions. In particular, the stainless steel model is suitable for environments where high hygienic standards are enforced, such as the chemical, pharmaceutical or food & beverage industry.

Characterized by their great resistance to corrosion, the galvanized and stainless steel hand pallet trucks are perfect for working in humid conditions or environments where high hygiene standards must be respected.



Stainless Steel Ergonomic Handle

Truck has a spring-loaded handle with a three position lever control (raise, lower, neutral) for easy operation and maneuvering.

Maximum Precision

The positioning of the weighing cells at the 4 end points of the forks ensures extremely precise weight recording up to a slanting position of 2°.

Multiple function keys

Its large-sized 6 digits LCD display provides accurate and precise weighing in kg and lb. Its software allows not only net/gross/tare weighing but also unit counting, adding and totalling of multiple loads. Weights are shown in 1 kg/lb steps with 0.05% precision.

Built-in Rechargeable Battery


Built-in 4000mAh super-capacity rechargeable battery with the advantages of durability and convenient charging, without disassembly. It lasts 3 months on a single battery charge. and the operating current is only 1ma (on the premise that backlight and printer connection are turned off).

High quality Wheels

Steering wheels and double roller wheels with paneling made of nylon, which is durable and more labor-saving which is suitable for uneven ground.

Easy Cleaning and High Resistance to Corrosion

Continuous welding, machinery and welding dust are cleaned by glass-fibre blasting process. Open fork, maximum hygienic, avoid hiding places for bacteria and allow an integral daily cleaning.



Model designation		HL20S (metric)	HL20S (imperial)	HL25S (metric)	HL25S (imperial)
Material		SUS304 stainless steel	SUS304 stainless steel	SUS304 AC stainless	SUS304 AC stainless
Capacity	kg lbs	2000 4400	4400	2500 5500	5500
Fork height	mm in	80-205 31-8	80-205 31-8	80-205 31-8	80-205 31-8
Steering wheel	mm in	φ180x50	φ180x50	φ180x50	φ180x50
Single load roller	mm in	φ74x93	φ74x93	φ74x93	φ74x93
Tandem load roller	mm in	φ74x70	φ74x70	φ74x70	φ74x70
Size of fork	mm in	160x60 6.3x2.36	160x60 6.3x2.36	160x60 6.3x2.36	160x60 6.3x2.36
Width over forks	mm in	550/680 21.6/27	550/680 21.6/27	550/680 21.6/27	550/680 21.6/27
Fork length	mm in	1150/1220 45/48	1150/1220 45/48	1150/1220 45/48	1150/1220 45/48
Battery		DC 6V/4.5Ah	DC 6V/4.5Ah	DC 6V/4.5Ah	DC 6V/4.5Ah
Charger		100V/240V	100V/240V	100V/240V	100V/240V
N.VV	kg lbs	100/108	233/238	122/124	268/273

Ingress Protection Standard System IP65, Indicator IP67
Automatic Switch-off Standard After 15 Minutes
Graduation 500-2200kg: 1kg
200-500kg: 0.5kg
0-200kg: 0.2kg
Maximum Inaccuracy ±1% Applied Weight

Built in printer for printing weight data on site is available on request.

Suitable for application in explosion hazardous area, protection according to ATEX II 2GD IIB 14T197°C X (Zones 1 and 21 & 2 and 22)