


## Defoamer

Cement defoamer  
Excellent foam control



## Product #: UBCem-541

### Introduction

- UBCem-541 a polyether defoamer for use in asbestos production processing applications. It will prevent foaming in virtually any industrial application.
- It acts quickly breaking up the foam without altering the effectiveness of the cleaning solution or effluent treatment chemicals being used.

### Application

- High temperature, alkali and acid resistance.
- Compatibility with cement: suitable almost any type of foam.
- Easy to disperse in the water.
- Normal dosage: 10 to 100ppm, the best amount of addition by the customer according to the specific situation of the test decision.

### Recommended Handling

- All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Material Safety Data Sheet (MSDS).

### Packaging and Storage

- Packed in 55gallon drum.
- Be kept away from moisture and possible damage of the packages in transportation, and stored in cool and dry situation.
- Life span is one and half years.

### Technical Index

Items	Specification
Appearance	Colorless to grey white liquid
pH value	5-8
Viscosity (25°C)	200~1000mPa.s
Uniformity	no delamination, allowing small suspended matter

For more information, Send email: [info@youzhuchem.com](mailto:info@youzhuchem.com), or call 0086 13408536218 or for information on other YouzhuCHEM products visit [youzhuchem.com](http://youzhuchem.com)