

Detergents

Downhole use in oil and gas wells for cleanup during the displacement, Rig cleaning...



Product #: UniKlean Pro

Introduction

UniKlean Pro is formulated from various high-efficiency surfactants and other additives. Nontoxic, odorless, and noncorrosive.

UniKlean Pro has strong permeability and can quickly penetrate into the mud cake formed on the wellbore during the drilling process, dispersing and eroding the mud cake, thereby improving. The bonding ability between cement slurry and the contact surface.

Technical Index

Properties	Specification
Appearance	Clear liquid
Specific Gravity (20 °C, g/cm ³)	0.90-0.98
Flash Point (°C, closed)	> 47
pH (@10% solution)	6.0-8.0

Application

- ✓ UniKlean Pro has strong washing and decomposition characteristics, which can effectively remove and displace polymeric substances in drilling fluid in wells, and effectively improve the bonding ability of cement slurry. It has good compatibility with completion mud.

Recommended Handling

- ✓ The recommended dosage is 10% to 20% in spacer fluid(v/w), while a pilot test is required for optimal results.
- ✓ All personnel handling this material must handle it as an industrial chemical, wearing protective equipment and observing the precautions as described in the Material Safety Data Sheet (MSDS).

Packaging and Storage

- 200L/Drum, or packaging according to customer requirement. Prevent packaging damage during storage and transportation. The storage period is one and half years.
- Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and /or stacking.

For more information, Send email: info@youzhuchem.com, or call 0086 13408536218 or for information on other YouzhuCHEM products visit youzhuchem.com