

设计(Design)		冼敏杰		2017. 11. 15		Dongguan Asite Technology Co., Ltd.
审核(Check)		张建党		2017. 11. 15		
批准(Confirm)						
部 门 (Department)		技 术 部 TechnologyDepartment				SPECIFICATION 规 格 书
版本 (Edition)	A/0	页次 (Page)	1/3			

客户(CUSTOMER):
 型号(PART NO.): SDL-BD0835A-24L10
 客户型号(CUSTOMER PART NO.):

1. 适用范围(scope)

本规格书仅适用于本公司的直流螺线管SDL-BD0835A-24L10(The specification only applies for the Tubular solenoid SDL-BD0835A-24L10 of our compang)

2. 产品特点(STANDARD TEST CONDITION)

- 2-1 双向旋转，断电自保持：内置高性能永磁体，能正反双向30-100度的往复高速旋转，在断电后并能实现自保持。(Two way rotation,power and self-maintenance: a high performance permanet magnet, can be positive and negative direction of the 30-100 degree of the reciprocating high-speed rotation,and can be achieved after the power.)
- 2-2 高响应速度：高达10-30ms的响应速度，实现机构高速旋转或定位；(High response speed: the response rate of up to 10-30ms, to achieve high-speed rotation, or positioning mechaanism;)
- 2-3 旋转角度可设定在30-100° 范围内。(Any operating angle within 30degree to 100degree can be set.)
- 2-4 无轴向位移，低噪音。外置挡板可防震减噪。(There is no movement along the axial and also stopper is located outside,wihich lower the noise .For the prouducts which as built-in stopper, the stopper material is examined to lower noise and librations.)

3. 外形图(APPLEARANCE)

- 3-1 外形尺寸:参照附图。图号:SDL-BD0835A-24L10
(DIMENSION SEE THE ATTACHMENT. DRAWING NO. SDL-BD0835A-24L10

4. 额定参数(RATED PARAMETER)

- 4-1 电 压(VOLTAGE): DC24V
- 4-2 电 流(CURRENT): 2.4A(at DC24V 20℃)
- 4-3 功 率(WATTAGE): 57.6W
- 4-4 直流电阻(DC RESISTANCE): 10Ω ±10%周围温度20℃(Ambiance temperature20℃)
- 4-5 工作循环(DUTY CYCLE): 5%通电(Electrify 25%)
- 4-6 绝缘等级(INSULATION CLASS): F类(BCLASS)

NO. 序号	Date 日期	Modify content 修 改 内 容	Revise 更改人	Check 审 核	NO. 序号	Date 日期	Modify content 修 改 内 容	Revise 更改人	Check 审 核
1					1				
2					2				