



A solution just for you

Flair Induction Heating&Melting Capacitor Specification Table

AC power water cooled capacitor

Model	Specification	Cooling method	Voltage	capacity	Frequency	capacitance	current	Terminal Nos	Diemension(mm)			Capacitor Shell		Insulating bushing	Weight
			KV	Kvar	kHz	uf	A		Length	Width	Height	Feature	Material		kg/pc
RFM	0.375-250-2.5	water cooling	0.375	250	2.5	113.1768484	666.66667	4	336	142	175	non-insulation	Aluminium	white porcelain	13.1
RFM	0.375-500-1(7)	water cooling	0.375	500	1	565.8842421	1333.3333	6	400	166	350	non-insulation	Aluminium	white porcelain	34.7
RFM	0.375-500-2.5	water cooling	0.375	500	2.5	226.3536968	1333.3333	6	336	142	325	non-insulation	Aluminium	white porcelain	23.6
RFM	0.375-750-1(9)	water cooling	0.375	750	1	848.8263632	2000	10	440	207	436	non-insulation	Aluminium	white porcelain	57.7
RFM	0.375-750-2.5(9)	water cooling	0.375	750	2.5	339.5305453	2000	8	336	142	400	non-insulation	Aluminium	white porcelain	29.2
RFM	0.375-1000-1(4)	water cooling	0.375	1000	1	1131.768484	2666.6667	10	440	207	470	non-insulation	Aluminium	white porcelain	63.9
RFM	0.375-1000-1.5	water cooling	0.375	1000	1.5	754.5123228	2666.6667	10	440	166	430	non-insulation	Aluminium	white porcelain	48.2
RFM	0.375-1000-2(9)	water cooling	0.375	1000	2	565.8842421	2666.6667	10	440	166	400	non-insulation	Aluminium	white porcelain	44.0
RFM	0.375-1000-2.5(9)	water cooling	0.375	1000	2.5	452.7073937	2666.6667	10	440	166	325	non-insulation	Aluminium	white porcelain	36.5
RFM	0.375-1000-4(9)	water cooling	0.375	1000	4	282.9421211	2666.6667	10	440	166	260	non-insulation	Aluminium	white porcelain	29.7
RFM	0.65-560-20	water cooling	0.65	560	20	10.54754652	861.53846	4	303	120	175	non-insulation	Aluminium	white porcelain	11.3
RFM	0.65-560-50	water cooling	0.65	560	50	4.21901861	861.53846	6	303	120	175	non-insulation	Aluminium	white porcelain	11.3
RFM	0.75-500-2.5	water cooling	0.75	500	2.5	56.58842421	666.66667	4	303	120	210	non-insulation	Aluminium	white porcelain	12.3
RFM	0.75-500-15	water cooling	0.75	500	15	9.431404035	666.66667	4	303	126	210	Insulation	Aluminium	white porcelain	13.0
RFM	0.75-560-4	water cooling	0.75	560	4	39.61189695	746.66667	4	303	120	240	non-insulation	Aluminium	white porcelain	13.6
RFM	0.75-640-8	water cooling	0.75	640	8	22.63536968	853.33333	4	303	120	175	non-insulation	Aluminium	white porcelain	11.0
RFM	0.75-720-1	water cooling	0.75	720	1	203.7183272	960	4	336	142	300	non-insulation	Aluminium	white porcelain	21.2
RFM	0.75-900-15(2)	water cooling	0.75	900	15	16.97652726	1200	6	336	166	240	Insulation	Aluminium	white porcelain	20.8



A solution just for you

RFM	0.75-900-15(3)	water cooling	0.75	900	15	16.97652726	1200	6	336	142	220	Insulation	Aluminium	white porcelain	17.4
RFM	0.75-1000-0.5	water cooling	0.75	1000	0.5	565.8842421	1333.3333	6	440	166	400	non-insulation	Aluminium	white porcelain	42.4
RFM	0.75-1000-1	water cooling	0.75	1000	1	282.9421211	1333.3333	6	336	142	400	non-insulation	Aluminium	white porcelain	28.0
RFM	0.75-1000-1(3)	water cooling	0.75	1000	1	282.9421211	1333.3333	6	336	166	325	non-insulation	Aluminium	white porcelain	27.0
RFM	0.75-1000-1(5)	water cooling	0.75	1000	1	282.9421211	1333.3333	6	336	166	350	non-insulation	Aluminium	white porcelain	28.3
RFM	0.75-1000-1.5(2)	water cooling	0.75	1000	1.5	188.6280807	1333.3333	6	336	142	285	non-insulation	Aluminium	white porcelain	20.7
RFM	0.75-1000-2(2)	water cooling	0.75	1000	2	141.4710605	1333.3333	6	336	142	285	non-insulation	Aluminium	white porcelain	20.3
RFM	0.75-1000-2.5	water cooling	0.75	1000	2.5	113.1768484	1333.3333	6	336	142	240	non-insulation	Aluminium	white porcelain	18.1
RFM	0.75-1000-3(2)	water cooling	0.75	1000	3	94.31404035	1333.3333	6	336	142	240	non-insulation	Aluminium	white porcelain	17.6
RFM	0.75-1000-4	water cooling	0.75	1000	4	70.73553026	1333.3333	6	336	142	240	non-insulation	Aluminium	white porcelain	18.8
RFM	0.75-1000-6	water cooling	0.75	1000	6	47.15702018	1333.3333	6	336	142	240	non-insulation	Aluminium	white porcelain	18.3
RFM	0.75-1000-6(2)	water cooling	0.75	1000	6	47.15702018	1333.3333	6	336	142	240	Insulation	Aluminium	white porcelain	19.0
RFM	0.75-1000-8	water cooling	0.75	1000	8	35.36776513	1333.3333	6	336	142	220	Insulation	Aluminium	white porcelain	17.5
RFM	0.75-1000-8(2)	water cooling	0.75	1000	8	35.36776513	1333.3333	6	336	142	210	non-insulation	Aluminium	white porcelain	16.3
RFM	0.75-1000-10	water cooling	0.75	1000	10	28.29421211	1333.3333	6	336	142	210	non-insulation	Aluminium	white porcelain	16.5
RFM	0.75-1000-11(2)	water cooling	0.75	1000	11	25.722011	1333.3333	6	336	142	220	Insulation	Aluminium	white porcelain	18.8
RFM	0.75-1500-1(9)	water cooling	0.75	1500	1	424.4131816	2000	8	440	166	350	non-insulation	Aluminium	white porcelain	37.5
RFM	0.75-1500-1.5(9)	water cooling	0.75	1500	1.5	282.9421211	2000	8	336	166	365	non-insulation	Aluminium	white porcelain	30.3
RFM	0.75-1500-2	water cooling	0.75	1500	2	212.2065908	2000	8	336	166	300	non-insulation	Aluminium	white porcelain	25.5
RFM	0.75-1500-2.5	water cooling	0.75	1500	2.5	169.7652726	2000	8	336	142	340	non-insulation	Aluminium	white porcelain	24.8
RFM	0.75-1500-3(2)	water cooling	0.75	1500	3	141.4710605	2000	8	336	142	285	non-insulation	Aluminium	white porcelain	21.5
RFM	0.75-1500-4(3)	water cooling	0.75	1500	4	106.1032954	2000	8	336	142	260	non-insulation	Aluminium	white porcelain	22.0



A solution just for you

RFM	0.75-1500-6(3)	water cooling	0.75	1500	6	70.73553026	2000	8	336	142	240	non-insulation	Aluminium	white porcelain	20.6
RFM	0.75-2000-0.5	water cooling	0.75	2000	0.5	1131.768484	2666.6667	12	440	210	560	non-insulation	Aluminium	white porcelain	74.3
RFM	0.75-2000-1(2)	water cooling	0.75	2000	1	565.8842421	2666.6667	10	440	207	410	non-insulation	Aluminium	white porcelain	53.3
RFM	0.75-2000-1(3)	water cooling	0.75	2000	1	565.8842421	2666.6667	10	390	205	415	non-insulation	Aluminium	white porcelain	47.9
RFM	0.75-2000-1(9)	water cooling	0.75	2000	1	565.8842421	2666.6667	10	440	166	465	non-insulation	Aluminium	white porcelain	49.8
RFM	0.75-2000-1.5(9)	water cooling	0.75	2000	1.5	377.2561614	2666.6667	10	440	166	365	non-insulation	Aluminium	white porcelain	39.6
RFM	0.75-2000-2	water cooling	0.75	2000	2	282.9421211	2666.6667	10	440	166	300	non-insulation	Aluminium	white porcelain	33.1
RFM	0.75-2000-2.5(9)	water cooling	0.75	2000	2.5	226.3536968	2666.6667	10	440	166	350	non-insulation	Aluminium	white porcelain	37.0
RFM	1.0-1000-0.5	water cooling	1	1000	0.5	318.3098862	1000	6	440	166	340	non-insulation	Aluminium	white porcelain	35.1
RFM	1.0-1000-1	water cooling	1	1000	1	159.1549431	1000	4	336	142	325	non-insulation	Aluminium	white porcelain	22.3
RFM	1.0-1000-1(2)	water cooling	1	1000	1	159.1549431	1000	6	336	142	295	non-insulation	Aluminium	white porcelain	20.8
RFM	1.0-1400-1	water cooling	1	1400	1	222.8169203	1400	6	336	166	350	non-insulation	Aluminium	white porcelain	28.0
RFM	1.0-2000-0.5(2)	water cooling	1	2000	0.5	636.6197724	2000	8	440	207	440	non-insulation	Aluminium	white porcelain	56.5
RFM	1.0-2000-0.7	water cooling	1	2000	0.7	454.7284088	2000	8	440	166	465	non-insulation	Aluminium	white porcelain	47.8
RFM	1.0-2000-1	water cooling	1	2000	1	318.3098862	2000	8	440	166	350	non-insulation	Aluminium	white porcelain	36.8
RFM	1.2-1000-1	water cooling	1.2	1000	1	110.524266	833.33333	4	336	142	300	non-insulation	Aluminium	white porcelain	20.6
RFM	1.2-1200-0.7	water cooling	1.2	1200	0.7	189.4701703	1000	6	440	166	300	non-insulation	Aluminium	white porcelain	30.6
RFM	1.2-1400-0.7	water cooling	1.2	1400	0.7	221.0485321	1166.6667	6	440	166	325	non-insulation	Aluminium	white porcelain	33.1
RFM	1.2-2000-0.5	water cooling	1.2	2000	0.5	442.0970641	1666.6667	8	440	207	436	non-insulation	Aluminium	white porcelain	54.5
RFM	1.2-2000-0.7(4)	water cooling	1.2	2000	0.7	315.7836172	1666.6667	8	440	166	420	non-insulation	Aluminium	white porcelain	43.4
RFM	1.2-2000-1(3)	water cooling	1.2	2000	1	221.0485321	1666.6667	8	440	166	325	non-insulation	Aluminium	white porcelain	33.7
RFM	1.4-2000-0.5	water cooling	1.4	2000	0.5	324.8060063	1428.5714	8	440	207	436	non-insulation	Aluminium	white porcelain	53.7



A solution just for you

RFM	1.4-2000-0.7	water cooling	1.4	2000	0.7	232.0042902	1428.5714	6	440	166	415	non-insulation	Aluminium	white porcelain	41.3
RFM	1.5-1000-1	water cooling	1.5	1000	1	70.73553026	666.66667	6	336	142	340	non-insulation	Aluminium	white porcelain	22.7
RFM	1.5-1000-2.5	water cooling	1.5	1000	2.5	28.29421211	666.66667	4	336	166	240	non-insulation	Aluminium	white porcelain	18.1
RFM	1.5-2000-0.5	water cooling	1.5	2000	0.5	282.9421211	1333.3333	6	440	207	436	non-insulation	Aluminium	white porcelain	51.7
RFM	1.5-2000-0.7	water cooling	1.5	2000	0.7	202.101515	1333.3333	6	440	166	410	non-insulation	Aluminium	white porcelain	40.3
RFM	1.5-2000-1	water cooling	1.5	2000	1	141.4710605	1333.3333	6	440	166	300	non-insulation	Aluminium	white porcelain	30.5
RFM	1.5-2500-2.5(2)	water cooling	1.5	2500	2.5	70.73553026	1666.6667	8	440	142	400	non-insulation	Aluminium	white porcelain	33.6
RFM	1.5-3000-1(2)	water cooling	1.5	3000	1	212.2065908	2000	8	440	166	430	non-insulation	Aluminium	white porcelain	43.3
RFM	1.5-4000-1(3)	water cooling	1.5	4000	1	282.9421211	2666.6667	10	440	207	410	non-insulation	Aluminium	white porcelain	51.4
RFM	1.6-2000-0.5(8)	water cooling	1.6	2000	0.5	248.6795986	1250	6	390	205	430	non-insulation	Aluminium	white porcelain	45.2
RFM	1.7-2000-0.5	water cooling	1.7	2000	0.5	220.2836583	1176.4706	6	440	207	436	non-insulation	Aluminium	white porcelain	51.8
RFM	1.2-2000-0.5(13)	water cooling	1.2	2000	0.5	442.0970641	1666.6667	8	440	207	436	non-insulation	Aluminium	white porcelain	54.4
RFM	1.4-2000-0.5(8)	water cooling	1.4	2000	0.5	324.8060063	1428.5714	1	390	205	440	Insulation	Aluminium	white porcelain	47.3
RFM	1.5-2000-0.5(3)	water cooling	1.5	2000	0.5	282.9421211	1333.3333	1	390	205	405	Insulation	Aluminium	white porcelain	43.9
RFM	1.5-3000-0.5(2)	water cooling	1.5	3000	0.5	424.4131816	2000	1	391	206	525	Insulation	Patterned Al	Black porcelain	56.4
RFM	1.6-2000-0.25(8)	water cooling	1.6	2000	0.25	497.3591972	1250	6	390	205	680	non-insulation	Aluminium	white porcelain	71.3
RFM	1.7-1500-0.25(8)	water cooling	1.7	1500	0.25	330.4254874	882.35294	4	390	205	615	non-insulation	Aluminium	white porcelain	62.5
RFM	1.7-2260-0.5(8)	water cooling	1.7	2260	0.5	248.9205338	1329.4118	6	390	205	430	non-insulation	Aluminium	white porcelain	46.2
RFM	1.8-3000-1	water cooling	1.8	3000	1	147.365688	1666.6667	8	440	166	436	non-insulation	Aluminium	white porcelain	43.1
Model	Specification	Cooling method	Voltage	capacity	Frequency	capacitance	current	Terminal Nos	Diemension(mm)			Capacitor Shell		Insulating bushing	Weight
			KV	Kvar	kHz	uf	A		Length	Width	Height	Feature	Material		kg/pc

Above 2KV water cooled capacitor



A solution just for you

RFM	2.5-2000-1(3)	water cooling	2.5	2000	1	50.92958179	800	1	390	178	330	Insulation	Aluminium	white porcelain	31.6
RFM	2.5-4000-1	water cooling	2.5	4000	1	101.8591636	1600	1	390	175	485	Insulation	Aluminium	Black porcelain	44.4
RFM	2.5-4850-1.5	water cooling	2.5	4850	1.5	82.34	1940	1	440	170	500	Insulation	Aluminium	white porcelain	51.9
RFM	2.2-2000-0.5(3)	water cooling	2.2	2000	0.5	131.5330108	909.09091	6	330	165	775	non-insulation	Aluminium	white porcelain	54.0
RFM	2.5-2000-0.3(8)	water cooling	2.5	2000	0.3	169.7652726	800	4	390	205	640	non-insulation	Aluminium	white porcelain	63.2
RFM	2.5-2000-0.5	water cooling	2.5	2000	0.5	101.8591636	800	1	390	205	390	Insulation	Aluminium	white porcelain	39.6
RFM	2.5-4000-0.5	water cooling	2.5	4000	0.5	203.7183272	1600	1	391	206	600	Insulation	Patterned Al	Black porcelain	61.0
RFM	2.5-4500-0.3	water cooling	2.5	4500	0.3	381.9718634	1800	1	320	302	910	Insulation	Aluminium	Black porcelain	112.0
RFM	2.8-5000-0.5	water cooling	2.8	5000	0.5	203.0037539	1785.7143	1	391	206	760	Insulation	Patterned Al	Black porcelain	75.8
RFM	2.8-6000-0.5	water cooling	2.8	6000	0.5	243.6045047	2142.8571	1	391	206	815	Insulation	Patterned Al	Black porcelain	82.5
RFM	2.5-5000-0.5	water cooling	2.5	5000	0.5	254.6479089	2000	1	559	203	560	Insulation	Patterned AL	Black porcelain	81.6
RAM	2.5-6000-0.3	water cooling	2.5	6000	0.3	509.2958179	2400	2	559	203	787	Insulation	Patterned AL	Black porcelain	112.2
RAM	2.5-6000-0.5	water cooling	2.5	6000	0.5	305.5774907	2400	1	559	175	665	Insulation	Patterned AL	Black porcelain	83.7
Model	Specification	Cooling method	Voltage	capacity	Frequency	capacitance	current	Terminal Nos	Diemension(mm)			Capacitor Shell		Insulating bushing	Weight
			KV	Kvar	kHz	uf	A		Length	Width	Height	Feature	Material		
Above 3KV water cooled capacitor															
RFM	3.0-3000-1(2)	water cooling	3	3000	1	53.0516477	1000	1	391	176	355	Insulation	Patterned AL	Black porcelain	32.5
RFM	3.0-3500-1(3)	water cooling	3	3500	1	61.89358898	1166.6667	1	391	176	405	Insulation	Patterned AL	Black porcelain	36.6
RFM	3.0-4000-1	water cooling	3	4000	1	70.73553026	1333.3333	1	390	178	500	Insulation	Patterned AL	Black porcelain	46.3
RFM	3.0-5000-1(2)	water cooling	3	5000	1	88.41941283	1666.6667	8	441	167	535	Insulation	Patterned AL	Black porcelain	51.4
RFM	3.0-13400-1.2	water cooling	3	13400	1.2	197.470022	4466.6667	2	560	218	775	Insulation	Patterned AL	Black porcelain	130.2
RFM	3.05-8682-0.7	water cooling	3.05	8682	0.7	212.1984437	2846.5574	2	559	203	711	Insulation	Patterned AL	Black porcelain	103.5



A solution just for you

RFM	3.2-4500-1	water cooling	3.2	4500	1	69.9411371	1406.25	6	391	167	530	Insulation	Patterned AL	Black porcelain	45.5
RFM	3.2-5000-0.6	water cooling	3.2	5000	0.6	129.5206243	1562.5	6	441	215	590	Insulation	Patterned AL	Black porcelain	70.2
RFM	3.2-6000-0.5	water cooling	3.2	6000	0.5	186.5096989	1875	8	441	208	715	Insulation	Patterned AL	Black porcelain	81.8
RFM	3.2-6000-0.7	water cooling	3.2	6000	0.7	133.2212135	1875	8	441	208	540	Insulation	Patterned AL	Black porcelain	62.8
RFM	3.5-3000-1	water cooling	3.5	3000	1	38.98	857	1	440	170	420	Insulation	Patterned AL	white porcelain	42.6
RFM	3.5-5000-0.5	water cooling	3.5	5000	0.5	129.9224025	1428.5714	6	441	215	755	Insulation	Patterned AL	Black porcelain	93.8
RFM	3.6-5000-0.5	water cooling	3.6	5000	0.5	122.80474	1388.8889	6	441	215	660	Insulation	Patterned AL	Black porcelain	82.6
RFM	3.6-5000-1	water cooling	3.6	5000	1	61.40237002	1388.8889	6	441	176	435	Insulation	Patterned AL	Black porcelain	47.2
RFM	3.6-6000-1	water cooling	3.6	6000	1	73.68284402	1666.6667	1	440	218	560	Insulation	Aluminium	white porcelain	69.6
RFM	3.0-3000-0.5(2)	water cooling	3	3000	0.5	106.1032954	1000	1	390	205	500	Insulation	Aluminium	Black porcelain	49.8
RFM	3.0-4000-0.5	water cooling	3	4000	0.5	141.4710605	1333.3333	1	391	206	555	Insulation	Patterned AL	Black porcelain	56.2
RFM	3.0-5000-0.5	water cooling	3	5000	0.5	176.8	1667	1	561	221	530	Insulation	Patterned AL	Black porcelain	81.1
RFM	3.2-4000-0.5(4)	water cooling	3.2	4000	0.5	124.3397993	1250	1	391	167	660	Insulation	Patterned AL	Black porcelain	54.5
RFM	3.2-5000-0.5(12)	water cooling	3.2	5000	0.5	155.4247491	1562.5	8	441	215	720	Insulation	Patterned AL	Black porcelain	84.0
RFM	3.3-6360-0.7	water cooling	3.3	6360	0.7	132.8	1927.27	1	561	211	720	Insulation	Aluminium	Black porcelain	110.5
RFM	3.3-7700-0.5	water cooling	3.3	7700	0.5	225.07	2333.3	1	561	211	890	Insulation	Patterned AI	Black porcelain	136.8
RAM	3.0-5000-0.5(2)	water cooling	3	5000	0.5	176.8388257	1666.6667	1	559	191	625	Insulation	Patterned AL	Black porcelain	90.4
RAM	3.0-6000-0.3(2)	water cooling	3	6000	0.3	353.6776513	2000	2	559	191	787	Insulation	Patterned AL	Black porcelain	104.8
RAM	3.0-6000-0.5(6)	water cooling	3	6000	0.5	212.2065908	2000	2	559	203	591	Insulation	Patterned AL	Black porcelain	83.5
RAM	3.0-7500-0.3	water cooling	3	7500	0.3	442.0970641	2500	1	559	203	940	Insulation	Patterned AL	Black porcelain	129.2
RAM	3.2-5000-0.3	water cooling	3.2	5000	0.3	259.0412485	1562.5	2	559	191	711	Insulation	Patterned AL	Black porcelain	94.3
RAM	3.2-5000-0.5(2)	water cooling	3.2	5000	0.5	155.4247491	1562.5	1	559	191	545	Insulation	Patterned AL	Black porcelain	78.9



A solution just for you

Model	Specification	Cooling method	Voltage	capacity	Frequency	capacitance	current	Terminal Nos	Dimension(mm)			Capacitor Shell		Insulating bushing	Weight kg/pc
			KV	Kvar	kHz	uf	A		Length	Width	Height	Feature	Material		
RAM	3.2-7000-0.5	water cooling	3.2	7000	0.5	217.5946488	2187.5	1	559	203	690	Insulation	Patterned AL	Black porcelain	105.1
RAM	3.4-7000-0.5	water cooling	3.4	7000	0.5	192.748201	2058.8235	1	559	203	780	Insulation	Patterned AL	Black porcelain	117.2
RAM	3.5-5200-0.5	water cooling	3.5	5200	0.5	135.1192986	1485.7143	1	559	175	630	Insulation	Patterned AL	Black porcelain	80.1
RAM	3.5-6000-0.5(2)	water cooling	3.5	6000	0.5	155.906883	1714.2857	2	559	203	591	Insulation	Patterned AL	Black porcelain	88.4
RAM	3.6-6000-0.5	water cooling	3.6	6000	0.5	147.365688	1666.6667	1	559	203	655	Insulation	Patterned AL	Black porcelain	94.5
RFM	3.8-7500-0.5	water cooling	3.8	7500	0.5	165.327157	1973.6842	1	559	203	845	Insulation	Patterned AL	Black porcelain	121.8
Above 4KV water cooled capacitor															
RFM	4.0-0.12-40	water cooling	4	483	40	0.12	120.75	1	170	126	150	Insulation	Aluminium	white porcelain	5
RFM	4.0-483-40(2)	water cooling	4	483	40	0.12	120.75	1	170	126	150	Insulation	Aluminium	white porcelain	5
RFM	4.0-0.22-30	water cooling	4	664	30	0.22	166	1	210	120	160	Insulation	Aluminium	white porcelain	6.3
RFM	4.0-691-23	water cooling	4	691	23	0.3	172.75	1	210	130	160	Insulation	Aluminium	white porcelain	7
RFM	4.0-694-23(2)	water cooling	4	694	23	0.3	173.5	1	210	130	160	Insulation	Aluminium	white porcelain	7
RFM	4.0-700-40	water cooling	4	700	40	0.174	175	2	170	126	150	Insulation	Aluminium	white porcelain	6
RFM	4.0-0.18-40	water cooling	4	724	40	0.18	181	1	210	120	160	Insulation	Aluminium	white porcelain	6.7
RFM	4.0-803-40	water cooling	4	803	40	0.2	201	2	170	126	150	Insulation	Aluminium	white porcelain	6.2
RFM	4.0-0.3-30	water cooling	4	905	30	0.3	226.25	1	210	120	160	Insulation	Aluminium	white porcelain	6.4
RFM	4.0-0.18-50	water cooling	4	905	50	0.18	226.25	1	210	120	160	Insulation	Aluminium	white porcelain	7.0
RFM	4.0-965-40	water cooling	4	965	40	0.23	241.25	2	170	126	150	Insulation	Aluminium	white porcelain	5.9
RFM	4.0-0.2-50	water cooling	4	1005	50	0.2	251.25	1	210	120	175	Insulation	Aluminium	white porcelain	6.7
RFM	4.0-0.34-30	water cooling	4	1025	30	0.34	256.25	1	290	120	160	Insulation	Aluminium	white porcelain	8.4



A solution just for you

RFM	4.0-0.4-30(3)	water cooling	4	1206	30	0.39	301.5	1	170	126	150	Insulation	Aluminium	white porcelain	5.7
RFM	4.0-0.42-30	water cooling	4	1267	30	0.42	316.75	1	303	120	160	Insulation	Aluminium	white porcelain	8.9
RFM	4.0-0.24×2-30	water cooling	4	1447	30	0.48	361.75	2	260	120	110	Insulation	Aluminium	white porcelain	6.1
RFM	4.0-0.48-30	water cooling	4	1448	30	0.48	362	1	290	120	175	Insulation	Aluminium	white porcelain	9.1
RFM	4.0-0.56-30	water cooling	4	1689	30	0.56	422.25	1	200	120	150	Insulation	Aluminium	white porcelain	7.1
RFM	4.0-0.6-30	water cooling	4	1810	30	0.6	452.5	1	303	120	180	Insulation	Aluminium	white porcelain	10.3
RFM	4.0-0.625-30	water cooling	4	1885	30	0.625	471.25	1	250	120	175	Insulation	Aluminium	white porcelain	9.3
RFM	4-0.32×2-30	water cooling	4	1930	30	0.64	482.5	2	260	120	110	Insulation	Aluminium	white porcelain	6.1
RFM	4.0-2011-20(2)	water cooling	4	2011	20	1	502.75	1	250	126	220	Insulation	Aluminium	white porcelain	12.6
RFM	4.0-2170-30(4)	water cooling	4	2170	30	0.72	542.75	1	303	126	165	Insulation	Aluminium	white porcelain	10.9
RFM	4.0-0.72-30(3)	water cooling	4	2171	30	0.72	542.75	1	210	126	175	Insulation	Aluminium	white porcelain	8.5
RFM	4.0-0.75-30	water cooling	4	2262	30	0.75	565.5	1	250	120	180	non-Insulation	Aluminium	white porcelain	8.6
RFM	4.0-0.8-30(2)	water cooling	4	2413	30	0.8	603.25	1	210	126	180	Insulation	Aluminium	white porcelain	8.8
RFM	4.0-0.84-30	water cooling	4	2533	30	0.84	633.25	1	303	126	220	Insulation	Aluminium	white porcelain	12.5
RFM	4.0-0.68-40	water cooling	4	2734	40	0.68	683.5	1	303	126	210	Insulation	Aluminium	white porcelain	12.1
RFM	4.0-2894-30(2)	water cooling	4	2894	30	0.96	723.75	1	303	126	185	Insulation	Aluminium	white porcelain	11.6
RFM	4.0-0.96-30	water cooling	4	2895	30	0.96	723.75	1	303	126	220	Insulation	Aluminium	white porcelain	13.9
RFM	4.0-1-30(2)	water cooling	4	3016	30	1	754	2	303	126	170	Insulation	Aluminium	white porcelain	11.5
RFM	4.0-1.2-30	water cooling	4	3619	30	1.2	904.75	1	303	150	210	Insulation	Aluminium	white porcelain	16.2
RFM	4.0-1.5-30	water cooling	4	4524	30	1.5	1131	1	336	150	220	Insulation	Aluminium	white porcelain	19.6
RFM	4.0-2-30	water cooling	4	6032	30	2	1508	1	336	126	350	Insulation	Aluminium	white porcelain	24.6
RAM	4.2-5000-0.3	water cooling	4.2	5000	0.3	150.3731511	1190.4762	1	559	203	711	Insulation	Patterned alumi	Black porcelain	101.7



A solution just for you

RFM	8.0-0.06-300	water cooling	8	7238	300	0.06	900	2	336	166	395	Insulation	Aluminium	Black porcelain	34.0
DC water cooled capacitor															
Model	Specification	Cooling method	Voltage	capacity	Frequency	capacitance	current	Terminal Nos	Dimension(mm)			Capacitor Shell		Insulating bushing	Weight kg/pc
			Kvdc	kvar	kHz	uf	A		Length	Width	Height	Feature	Material		
DZMJ	0.3-25000	water cooling	0.3			25000	2800	6	325	205	590	Insulation	Patterned AL	Black porcelain	48.4
DZMJ	0.86-1600	water cooling	0.86			1600	1000	1	320	135	475	Insulation	Aluminium	white porcelain	26.2
DZMJ	0.86-1850	water cooling	0.86			1850	1200	1	320	135	530	Insulation	Aluminium	white porcelain	28.9
DZMJ	0.86-3000	water cooling	0.86			3000	1500	1	440	135	490	Insulation	Aluminium	white porcelain	35.8
DZMJ	0.9-1850	water cooling	0.9			1850	1200	6	336	136	495	Insulation	Aluminium	white porcelain	30.2
DZMJ	0.9-3000(3)	water cooling	0.9			3000	1500	1	445	137	425	Insulation	Patterned AL	white porcelain	33.4
DZMJ	0.9-3000	water cooling	0.9			3000	1200	1	390	178	455	Insulation	Aluminium	white porcelain	39.5
DZMJ	0.9-3000(2)	water cooling	0.9			3000	1800	1	391	126	585	Insulation	Patterned AL	Black porcelain	37.6
DZMJ	0.9-4000(2)	water cooling	0.9			4000	2000	1	391	193	380	Insulation	Patterned AL	Black porcelain	36.1
DZMJ	0.9-5000	water cooling	0.9			5000	2000	1	440	192	545	Insulation	Aluminium	white porcelain	54.7
DZMJ	0.9-5000(3)	water cooling	0.9			5000	2500	1	391	183	485	Insulation	Patterned AL	Black porcelain	43.3
DZMJ	0.9-6000	water cooling	0.9			6000	2800	1	559	133	570	Insulation	Patterned AL	Black porcelain	53.5
DZMJ	1.2-1850	water cooling	1.2			1850	1200	1	340	192	500	Insulation	Aluminium	white porcelain	38.1
DZMJ	1.2-3000(2)	water cooling	1.2			3000	1500	1	391	136	510	Insulation	Patterned AL	Black porcelain	34.5
DZMJ	1.2-4000(2)	water cooling	1.2			4000	2000	1	391	193	495	Insulation	Patterned AL	Black porcelain	45.3
DZMJ	1.2-5000(5)	water cooling	1.2			5000	2500	1	559	145	591	Insulation	Patterned AL	Black porcelain	58.2
DZMJ	1.2-7000	water cooling	1.2			7000	3600	1	559	145	755	Insulation	Patterned AL	Black porcelain	75.5
DZMJ	1.3-2000	water cooling	1.3			2000	1800	1	391	126	495	Insulation	Patterned AL	Black porcelain	32.8



A solution just for you

DZMJ	1.3-3000	water cooling	1.3			3000	2000	1	391	136	510	Insulation	Patterned AL	Black porcelain	34.4
DZMJ	1.3-6000	water cooling	1.3			6000	3000	1	559	141	825	Insulation	Patterned AL	Black porcelain	79.9
DZMJ	1.35-5000	water cooling	1.35			5000	2500	1	560	141	680	Insulation	Patterned AL	Black porcelain	65.2
DZMJ	1.4-3000	water cooling	1.4			3000	1500	1	420	183	635	Insulation	Patterned AL	Black porcelain	60.5
DZMJ	1.5-1950	water cooling	1.5			1950	1500	1	440	140	775	Insulation	Aluminium	white porcelain	57.3
DZMJ	1.6-1950	water cooling	1.6			1950	2000	1	390	192	735	Insulation	Aluminium	white porcelain	65.2
DZMJ	1.6-2000	water cooling	1.6			2000	1200	1	440	192	530	Insulation	Aluminium	white porcelain	54.1
DZMJ	1.8-1850	water cooling	1.8			1850	1500	1	343	238	780	Insulation	Aluminium	white porcelain	71.4
DZMJ	1.8-4000	water cooling	1.8			4000	2000	1	559	141	780	Insulation	Patterned AL	Black porcelain	73.3
DZMJ	1.85-5200	water cooling	1.85			5200	3300	10	559	168	760	Insulation	Patterned AL	Black porcelain	85.2

Air cooled capacitor

Model	Specification	Cooling method	Voltage	capacity	Frequency	capacitance	current	Terminal Nos	Diemension(mm)			Capacitor Shell		Insulating bushing	Weight kg/pc
			kv	kvar	kHz	uf	A		Length	Width	Height	Feature	Material		
RFM	0.75-180-1	Air cooled	0.75	180	1	50.92958179	240	2	336	120	215	Insulation	Aluminium	white porcelain	12.8
RFM	0.75-250-2.5(2)	Air cooled	0.75	250	2.5	28.29421211	333.33333	2	303	115	200	Insulation	Aluminium	white porcelain	10.4
RFM	1.0-1244-3	Air cooled	1	1244	3	66	1244	6	440	140	300	Insulation	Aluminium	white porcelain	30.1
BFM	1.05-76-0.05	Air cooled	1.05	76	0.05	219.424502	72.380952	1	336	158	300	Insulation	Aluminium	white porcelain	21.6
RFM	1.3-1062-2	Air cooled	1.3	1062	2	50	816.92308	4	440	165	300	Insulation	Aluminium	white porcelain	32.7
RFM	1.7-1500-0.15	Forced-ventilation	1.7	1500	0.15	550.7091456	882.35294	4	440	205	635	Insulation	Aluminium	white porcelain	76.0
RFM	1.7-2260-0.5(4)	Forced-ventilation	1.7	2260	0.5	248.9205338	1329.4118	6	390	205	445	Insulation	Aluminium	white porcelain	49.8
RFM	1.7-3000-0.25	Forced-ventilation	1.7	3000	0.25	660.8509748	1764.7059	8	440	285	595	Insulation	Aluminium	white porcelain	100.7



A solution just for you

RFM	2.0-1252-3	Air cooled	2	1252	3	16.6	626	3	400	140	280	Insulation	Aluminium	white porcelain	22.5
RFM	1.2-200-0.05	Air cooled	1.2	200	0.05	442.0970641	166.66667	1	390	165	530	Insulation	Aluminium	white porcelain	45.1
RFM	1.5-200-0.05	Air cooled	1.5	200	0.05	282.9421211	133.33333	1	390	165	530	Insulation	Aluminium	white porcelain	43.4
RFM	1.7-1500-0.15	Forced-ventilation	1.7	1500	0.15	550.7091456	882.35294	4	440	205	635	Insulation	Aluminium	white porcelain	76.0
RFM	1.7-1500-0.25	Forced-ventilation	1.7	1500	0.25	330.4254874	882.35294	4	390	205	615	Insulation	Aluminium	white porcelain	64.1
RFM	2.5-2000-0.15	Forced-ventilation	2.5	2000	0.15	339.5305453	800	4	440	205	730	Insulation	Aluminium	white porcelain	83.9
RFM	2.5-3000-0.3(12)	Forced-ventilation	2.5	3000	0.3	254.6479089	1200	5	390	205	615	Insulation	Aluminium	white porcelain	65.0

Wuxi Flair Electronic Ltd