

6-EVF-50 (12V50AH/20HR)

LONG WAY 6-EVF-50 is one of the Deep Cycle battery of LONGWAY BATTERY.

This series adopts AGM technology, which has high safety & reliability, maintenance-free, high charging rate, low self-discharge, and long life.

Applications: Electric vehicles, Electric scooter, Electric wheel chair, Electric play car for children Sanitation vehicles and police patrol car etc.



Specifications: Designed according with the IEC60254-2014

12Volts (6 Cells per unit) Nominal Voltage

Nominal Capacity @25°C (77°F)

20hr -rate (2.25A) 50.0Ah @1.75V per cell@25°C 10Hr-rate (4.50A) 45.0AH @1.75V per cell@25°C 42.0AH @1.70Vper cell@25°C 5Hr-rate (7.65A) 35.0AH @1.70Vper cell@25℃ 3Hr-rate (11.2A)

Approx.14.2 ± 3%kg(35.27lbs) Internal Resistance

Approx. 6.50mΩ full charged @25°C

Maximum Discharge Current 400A(3sec)

Discharge: -20°C~50°C; Charge: 0°C~40°C Operating Temperature Range

Storage: -20°C~40°C

Equalization and Cycle Service 14.40~15.0VDC/unit Average @ 25°C

Maximum Charging Current 11.50A **Terminal** I4 (M6 stem)

Weight

Container Material ABS (UL 94-HB) & Flame Retardant (94-V0)

available upon request

Self Discharge LONGWAY batteries can be stored for more than 6

months and the Self-discharge ratio less than 3%per month at 25℃.Please charge batteries before using.



ISO9001:2015 ISO14001:2015 ISO45001:2018 ISO50001:2011

APPLICATION STANDARDS


- ISO 7176-25 2013
- IEC 60254-1- 2005
- SAE J1495-2018
- UL1989 (MH46789)


Terminal Type

Dimensions


Outer Dimensions 196


Length:196 \pm 2mm Width:166±2mm Height: 175±2mm Total Height: 175±2mm






Cycle Service Life







Kaiying Power Supply & Electrical Equip Co., Ltd

Add: Laogang Industrial Area, Chengxiang Town , Anxi, Quanzhou City, Fujian Province , China

Tel: 0595-68782266 Fax: 0595-68782222 Web: www.longwaybattery.com Email: sales@longwaybattery.com KY-IOP-6-EVF-45 A1, May 2022