



Hybrid Ac/dc



Solar Mppt



SVPWM Control



Full DC Inverter tech

Solar AC Cassette type



Technical Specifications

Tropical Applicable



 **ACDC R32**

Items	Unit	18000BTU	24000BTU
Mode		DCaWA1-ACDC-18KR2	DCaWMB3-ACDC-24KR2
Solar Power Voltage/ISC	V/A	80~380V/≤14A	150~380V/≤14A
Grid Power Voltage	V/Hz	208V~240V/50~60Hz	208V~240V/50~60Hz
Cooling Capacity	BTU	17600(4050~19800)	22000(6100~24200)
Cooling power input	W	1400(220~1750)	1865(300~2330)
Heating Capacity	BTU	17600(4050~19800)	25200(6100~27700)
Heating power input	W	1310(220~1400)	2000(320~2500)
EER	BTU/W	12.57	11.80
Indoor unit Dimension (WxHxD)	mm	830x830x230	830x830x230
Indoor unit Packing (WxHxD)	mm	925x925x230	925x925x290
Indoor panel Dimension(WxHxD)	mm	950x950x45	950x950x45
Indoor panel Packing(WxHxD)	mm	1030x1030x90	1030x1030x90
Outdoor unit Dimension (WxHxD)	mm	802x564x323	900x700x337
Outdoor unit Packing (WxHxD)	mm	910x622x405	1006x755x418

