



# SURVEILLANCE TRAILER TOWER SXC9 SERIES

---



**ZERO**  
emission



**ZERO**  
noise



**ZERO**  
fuel consumption



**ZERO**  
maintenance





**GRANDWATT**

## SURVEILLANCE TRAILER TOWER

2 or 4 Cameras record more than 60 days

Solar panel 3\*450 W Mono

Hot galvanizing mast 8 meters



Manual Lifting system



Manually sun angle 30°-41° adjustable with jack



Fork-lift Slots



RJ45

RJ45



eBox-WiFi-01




APP



# GRANDWATT

## SURVEILLANCE TRAILER TOWER



Standard Model		SXC9-R1350-2	SXC9-R1350-4	
Dimensions & Weight	Trailer Length/Length for Loading	3,087 mm (10'1½")/2,552 mm (8'4½")		
	Trailer Width/Width for Loading	1,651 mm (5'5")/ 1,540 mm (5'½")		
	Max. Length × Max. Width	3,087 mm (10'1½") × 3,534 mm (11'7")		
	Trailer Height/Height for Loading	2,540 mm (8'4")/2,540 mm (8'4")		
	Height Fully Extended	8m ( 26'3" )		
	Gross Weight	1,320 kg(2,910 lb)	1,350 kg(2,976 lb)	
Solar Panel & Battery System	System Voltage	48 VDC		
	Solar Panel System	1350 W- 3*450 W Mono		
	Retractable Panel System	Manual sliding system with guide rail		
	Solar System Sunshine Tilt	Manually 30°- 41° adjustable with a jack		
	Solar Controller	1*35 A MPPT controller		
	Lithium Battery	48V 230Ah Lithium battery	48V 350Ah Lithium battery	
Mast	Mast Style	5 sections; 2,500 lb manual winch		
Recommend Camera**	Max. Resolution	2560 × 1440		
	Focal Length	4.7 mm to 141 mm		
	Supplement Light Range	IR Distance, up to 100 m		
	Movement Range (Pan)	360°		
	Camera Quantity	2	4	
NVR Network System	Network Interfaces	4 independent PoE network interfaces		
	Playback	4-ch synchronous playback		
	Video Output	HDMI video output at up to 4K resolution		
	Hard Drive Capacity	8TB, can record for more than 60 days	14TB, can record for more than 60 days	
	Router	Supports 4G network, supports APN/VPDN, Sim card		
Trailer	Suspension & Brake	Single leaf-spring axle without brake		
	Tow Bar	"I" style		
	Forklift Slots	2 sides		
	Stabilizing Leg	5 jacks, 1 front, 2 rear & 2 side		
	Wheel	16" rim with regular tire		
	Tow Coupler	Switchable 2" ball coupler with 2½" pintle ring		
	Taillights	US Standard Tail Lights		
	Max Towing Speed	100 km/h (62 mph)		
General Data	Max. Wind Resistance (All solar panels retracted)	72km/s (45 mph)		
	Max. Quantity for loading in 40' high cube	7		
Optional parts or Accessories	Battery Charger with cable & plug	1 PCS		
	Generator Set	1 PCS		



GRANDWATT

**GRANDWATT ELECTRIC CORP.**

Address: 105 Professional Parkway, Suite 1502 Yorktown, VA 23693, USA  
[www.grandwatt.com](http://www.grandwatt.com)