

Model	S2600WP-16G-2TS
Product	Full Gigabit 2SFP+18GE L2+ Managed PoE Switch
Fixed Port	16*10/100/1000Base-TX PoE port(Data/Power) 2*10/100/1000Base-TX uplink RJ45 port(Data) 2*100/1000M SFP
PoE Ports	1-2 port supports IEEE802.3af/at/poe++/bt, max 90W/port PoE out 3-16 port supports IEEE802.3af/at, max 30W/port, PoE out
Console port	1*console port
Reset Key	1
PoE Pin	Af/at/bt: 12+ 45+ ; 36- 78- Af/at: 12+ 36-
PoE Bridge	Max 300W
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	56G/128Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	POWER:Power LED 19-20:SFP connection indicator Uplink:(10/100M=Green Link、 1000M=Orange Link) Downlink:(10/100M=Green Link、 1000M=Orange Link)
Power	Built-in power AC： 100-240Vac 50-60Hz 3.8A max 315W
Operating Temperature/Humidity	-10～+55℃； 5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃； 5%～95% RH Non coagulation
Product /Packing size(L*W*H)	293mm*190mm*45mm 410mm*278mm*95mm
N.W/G.W(kg)	1.7kg/2.4kg
Lightning Protection level	6KV 8/20us； IP30
Installation	Rack-mount(optional machine hanger spare parts)
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)