

Model	S500W-5G-SE
Product name	5 Port Gigabit Smart WEB Switch
Fixed Port	5*10M/100M/1000M RJ45 port
Network protocol	IEEE802.3 IEEE802.3i 10BASE-T IEEE802.3u 100BASE-TX IEEE 802.3z 1000BASE-X IEEE802.3x IEEE 802.3z 100BASE-X
Bandwidth	10Gbps
Packet Forwarding	7.2Mpps
MAC	2K
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(≤100 meter) 1000BASE-TX：Cat6 or later UTP(≤1000 meter)
LED Indicator	PWR: Power LED 1-5: (Network connection indicator light 10/100/1000M)
Power	External switch power supply DC: 12V 0.5A
Operating Temperature /Humidity	-10~+55℃；5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75℃；5%~95% RH Non coagulation
size	Product :87mm*83mm*25mm Packing:100mm*103mm*62mm
N.W/G.W (kg)	0.2kg/0.3kg
Installation	Desktop
Certificate	CE mark, commercial；CE/LVD EN60950；FCC Part 15 Class B；RoHS
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.