

Model	S600WP-5GT-2S+
Product	10G uplink 5-Port 2.5G L3 Convergence POE Managed Switch
Fixed Port	4*10/100/1000/2500M PoE 1*10/100/1000/2500M Uplink RJ45 2*100/1000/2500/10000M SFP
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 2-4 port supports IEEE802.3af/at, max 30W/port, PoE out
Console port	1*console port
Reset Key	1
PoE Pin	Af/at/bt: 12+ 45+ ; 36- 78- Af/at: 12+ 36-
PoE Bridge	Max 65W
CPU	MIPS-34Kc dual-core 800MHz
DDR	4G DDR3
FLASH	512MBytes
RAM	512MBytes
Bandwidth	512Gbps
Packet Forwarding	89.28Mpps
MAC	32K
Buffer	16 Mbit SRAM Packet Buffer
Jumbo Frame	Jumbo frame up to 12KB
VLAN Address	4K
Link Aggregation	Supports 128 trunk groups with up to 8 members per group
L3 Routing	IPV4 supports 12K; IPV6 supports 12K;
QoS Queue	8
Transmission Distance	10BASE-T ： Cat3,4,5 UTP(≤250 meter) 100BASE-TX ： Cat5 or later UTP(150 meter) 1000BASE-TX ： Cat6 or later UTP(150 meter) 2500BASE-TX ： Cat6 or later UTP(100 meter) SFP:100M/1G/10G single-mode multi-mode optical module, the maximum distance is ≤120km (depending on the optical module)
LED Indicator	PWR:Power LED SYS:System LED 1-5:10/100/1000、 2500M Network connection indicator 6-7:10/100/1000/2500M、 10000M SFP connection indicator PoE:Orange PoE indicator
Power	External power DC： 52V 1.25A max 71W(AC:100-240Vac 50/60Hz 0.9A)
Operating Temperature/Humidity	-10～+55℃； 5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃； 5%～95% RH Non coagulation
Product /Packing size(L*W*H)	220mm*112mm*30mm 265mm*220mm*68mm
N.W/G.W(kg)	0.8kg/1.3kg
Lightning Protection level	6KV 8/20us； IP30
Installation	Desktop
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)