

Model	G1200WP-8G-10S
Product name	Full Gigabit 8+10 L2+ Managed PoE Switch
Fixed Port	8*10/100/1000M RJ45 PoE 10*1000M SFP
PoE port	1 port supports IEEE802.3af/at/poe++/bt, with a maximum power of 90W per port 2-8 ports support IEEE802.3af/at, with a maximum single port power of 30W
Console port	1
Reset Key	1
PoE Pin	Af/at/bt: 1245+ ; 3678- Af/at: 12+ 36-
PoE Bridge	Max 300W
DDR	1G DDR3
FLASH	16MB
RAM	16MB
Bandwidth	56Gbps
Packet Forwarding	40.66Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10 Mbps: Cat3,4,5 UTP (≦ 250 meters) 100 Mbps: Cat5 or later UTP (150 meters) 1000 Mbps: Cat6 or later UTP (150 meters) SFP: Supports 1000M single mode multimode optical modules, with a maximum distance of ≦ 120km (depending on the optical module)
LED Indicator	POWER: Power indicator light HW: -- 9-18: Optical port connection indicator light Port orange: PoE indicator light Port green: Link indicator light
Power input	V1:37-57V 5A MAX V2:37-57V 5A MAX IN:--
Operating Temperature/Humidity	-40~+75°C； 10%~90% RH No coagulation
Storage Temperature/Humidity	-40~+85°C； 5%~95% RH No coagulation
Product Size/ Packing Size （L*W*H）	208mm*130mm*50mm 280mm*165mm*79mm
N.W/G.W(kg)	1.23kg/1.4kg
Installation	DIN guide rail type(additional wall hangers)
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.