

Industrial

8+4 Managed Switch

➤ **User Manual**

Industrial 8GE PoE+2TS

Overview


Industrial managed PoE switch series feature the performance on an industrial level, which can withstand severe working environment. With rich series and flexible port configuration, the switches are suitable for using requirements in various industrial field. Owing to a unique and special industry management interface, the switches provide a comprehensive security system, perfect ring network application, QoS strategy and rich VLAN function. It is convenient to manage and maintain which is satisfied in complex environment with high density such as in factories, mines, industry automation, transportation, infrastructure, port and farmlands. High-power PoE power supply and intelligent management function are applied in various network.

Features


- ◆ Unique industrial management interface, achieving high-efficiency network management.
- ◆ Lightning protection: up to 6KV.
- ◆ ESD Static protection: up to 8KV.
- ◆ Support industrial operation temperature: -40°C~80°C;
- ◆ Industrial operation humidity: 10%~90% RH non coagulation.
- ◆ Wide voltage input: 12-57V(SW)/ 37-57V(PoE).
- ◆ Unique ring network formation with one button to achieve quick application.
- ◆ Unique advanced PoE dog function (only for PoE model).

Display & Description

Industrial 8GE PoE+2TS 8*10/100/1000M PoE port+2*1000M optical port+2*1000M SFP



Ring Network Button SFP Optical port Console Port



Reset Key

Alarm Input+
Alarm Input-
Alarm Input-(second group of DC+)
Alarm Input-(second group of DC-)
Alarm Input-(first group of DC+)
Alarm Input-(first group of DC-)

Indicator


Indicator(Front)		Status	Description
PWR:Power/system LED		Always ON	System in loading(<30S)/System crashed(>30S)
		Always OFF	Power unconnected
		Flicker for 1S	System in normal operation
PoE Port Indicator (Port 1~8) Industrial 8GE PoE+4SFP	PoE-Orange	Always ON	Powered device connected and power supply normal
		Always OFF	No powered device connected or no power supply
	Link-Green	Always ON	Network signal communicated
		Always OFF	Network signal not communicated

Function Indicator(Front)	Status	Description
9-12:SFP LED	Always ON	SFP connected
	Always OFF	SFP not connected or abnormal
V1: Master power LED	Always ON	Master power is normal and in power supply
	Always OFF	No master power input
	Flicker for 1/4s	Power and voltage abnormal
	Flicker for 1s	Power and voltage normal(in reserve)
V2: Slave power LED	Always ON	Slave power is normal and in power supply
	Always OFF	No slave power input
	Flicker for 1/4s	Power and voltage abnormal
	Flicker for 1s	Power and voltage normal(in reserve)

Installation


DIN Guide Rail

- Insert the top of DIN guide rail into the groove at the bottom of rigid metallic spring.



Wall-mounting


- Install the wall hangers onto the switch.
- Secure the switch length onto the wall by using screws.



Attentions

- Please read the user manual detailed before using the switch, or improper operation can cause damage to machine components.
- Do not use it in the place near fire source.
- Do not throw it into the water neither do not wet the inner machine components.
- Do not short circuit the positive and negative poles of the battery with metal conductor.
- Do not dismantle or disassemble inner components, or factory will not underwrite the warranty stipulation.

Product List



Hardware Parameter

Model	Industrial 8GE PoE+2TS
Product	Industrial 8+4 Managed Switch
Console Port	1
Reset Key	1
Downlink Port	8*10/100/1000M Port 5~8 support AT PoE
Uplink Port	2*10/100/1000M SFP
Function Interface (only for enhancement model)	<p>1: 1 switch for quick formation of ring network.</p> <p>2: 2 group of independent power input, having under- and over-voltage protection.</p> <p>3: 1 group of wide voltage alarm input at a range of DC5-57V.</p> <p>4: 1 group of alarm output and relay output, can define various custom condition trigger.</p> <p>5: 1 group of environmental temperature and humidity detection, can make real-time monitoring of the environment.</p> <p>6: Real-time system of crucial voltage monitoring and alarm output function</p> <p>7: Real-time system temperature, environment temperature, humidity and alarm output function.</p> <p>8: Real-time detection and display of input voltage, current, power.</p> <p>9: Multiple custom port control and intelligent management.</p>
Network protocol	<p>IEEE 802.3x</p> <p>IEEE 802.3, IEEE 802.3u, IEEE 802.3ab,</p> <p>IEEE 802.3z</p> <p>IEEE 802.3ad</p> <p>IEEE 802.3q, IEEE 802.3q/p</p> <p>IEEE 802.1w, IEEE 802.1d, IEEE 802.1S</p> <p>IEEE 802.3z 1000BASE-X</p> <p>STP(Spanning Tree Protocol)</p> <p>RSTP/MSTP(Rapid Spanning Tree Protocol)</p> <p>EPPS ring network protocol</p> <p>EAPS ring network protocol</p> <p>hasivo 802.3AF/AT/HiPoE/BT</p> <p>hasivo AUTO 24V/48V PSE</p>
Environment Detection	1 group of input detection of environment temperature and humidity
Port Specification	1-8 port 10/100/1000BaseT(X)auto detection, AUTO-MDI/MDI-X
Transmission Mode	Store and Forward(full wirespeed)
Bandwidth	128Gbps
Packet Forwarding	40.32Mpps
MAC	8K
Buffer	4.1M
Transmission Distance	<p>10BASE-T : Cat3,4,5 UTP(≤250 meter)</p> <p>100BASE-TX : Cat5 or later UTP(≤100 meter)</p> <p>1000BASE-TX : Cat6 or later UTP(≤1000 meter)</p> <p>1000BASE-SX: 62.5 μm/50 μm MMF(2m~550m)</p> <p>1000BASE-LX: 62.5 μm/50 μm MM(2m~550m) or 10 μm SMF(2m~5000m)</p> <p>BIDI supported</p>
FLASH	16M
RAM	128M
Watt	<p>Standby power consumption≤15W</p> <p>Network full load power consumption=25W</p> <p>Full load power consumption=360W</p>
LED Indicator	<p>9-12:(SFP LED)</p> <p>PoE Port 1-2:(Green=48V; Orange=24V);</p> <p>Link port(Green=100M; Orange=1000M)</p> <p>Port 3-8(Green=100M; Orange=1000M)</p> <p>PWR:(Power/system LED)</p> <p>V1: (Master power LED)</p> <p>V2: (Slave power LED)</p> <p>HW:(Ring network ON LED)</p>
Power Input	<p>2 group of independent power input</p> <p>SW: DC 12-57V ; PoE: DC 37-57V</p>
Operating Temperature /Humidity	-40 ~ +80°C; 10% ~ 90% RH No coagulation
Storage Temperature /Humidity	-40~+85°C; 5%~95% RH No coagulation
Lightning Protection Level	6KV 8/20us, 8KV ESD; IP40
Product Size(L*W*H)	188mm*130mm*50mm
N.W(kg)	1.3kg
Installation	DIN guide rail(additional wall hangers accessoried)
Certificate	3C; CE mark, commercial; CE/LVD En60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

Software Parameter

Model	Industrial 8GE PoE+2TS
Monitoring Platform	Quick formation of ring network with one button System temperature monitoring and alarm External temperature and humidity monitoring and alarm Input power monitoring and alarm System each channel key voltage monitoring and alarm System total current, total power monitoring and alarm All-Port network monitoring and alarm Support one group input and output signal monitoring and alarm
Network Protocol	IEEE 802.3x IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z IEEE 802.3ad IEEE 802.3q, IEEE 802.3q/p IEEE 802.1w, IEEE 802.1d, IEEE 802.1S, IEEE 802.1X
MAC	Support 16K MAC address, auto aging and learning
VLAN Configuration	Support port-based VLAN Up to 4096 VLANs Support Voice VLAN, can configure Qos for voice data 802.1Q VLAN
Spanning Tree	STP(Spanning tree protocol); RSTP/MSTP(Rapid spanning tree protocol) EPPS/EAPS(Ring network protocol); 802.1x
Port Aggregation	Support 8 groups of aggregation, each group support up to 8 ports;
Port Mirroring	Support many-to-one port mirroring
Loop Guard	Support loop protection, real-time detection, quick alarm, concise location, Intelligent blocking, automatic recovery
Port Isolation	Support downlink ports isolate from each other and communicate with uplink port as well
Flow Control	Half duplex based on Back pressure; Full duplex based on PAUSE frame
Speed Limitation	Bandwidth management based on port input and output
Multicast Control	IGMPv1/2/3 and MLDv1/2 Snooping GMRP protocol registration Multicast address management, multicast VLAN, multicast routing port, static multicast address
DHCP	DHCP Snooping
Storm Suppression	Support unknown unicast, multicast, unknown multicast, broadcast type storm suppression Storm suppression based on bandwidth adjustment and storm filtering
Security	Support User port+IP address+MAC address; ACL based on IP, MAC; Support security properties of number of MAC address based on port
QOS	802.1p port queue priority algorithm; Cos/Tos, QOS remark WRR(Weighted Round Robin), weighted priority rotation algorithm; WRR?SP?WFQ priority scheduling modes
Cable Sequence	Auto-MDIX; auto detection on straight-through and cross-over cable
Negotiation Mode	Port support auto negotiation function(self-negotiation transmission rate and duplex mode)
System maintenance	Upgrade package upload; System log viewing; WEB recovery factory configuration
PoE Function (only for PoE models)	Port switch Schedule arrangement, timing switch Voltage, current, power display System total power display and configuration PoEdog: support auto reset, timing reset and ip binding reset when device failed Port power configuration(AF, AT HiPoE, BT) Indication of over power Port PoE type configuration(48V/24V power supplying)
Network Management	WEB interface management; CLI management based on Telnet, TFTP, Console; SNMP V1/V2/V3 management RMONV1/V2 management; RMON management

The followings are main functions not included in all the functions. Please contact with us for more other information
We support software development for customization requirement.