

<div><div>hasivo®</div><div>Hardware specifications</div></div>	
Model	G2600W-16G-2S
Product name	Industrial 2+16 Full Gigabit Managed Switch
Fixed Port	16 10/100/1000Base TX RJ45 ports (Data) 2 1000M optical ports
Management port	1*console port
Reset key	1
Network protocol	IEEE 802.3x IEEE 802.3、 IEEE 802.3u、 IEEE 802.3ab、 IEEE 802.3z IEEE 802.3ad IEEE 802.3q 、 IEEE 802.3q/p IEEE 802.1w、 IEEE 802.1d 、 IEEE 802.1S IEEE 802.3z 1000BASE-X STP(Spanning Tree Protocol) RSTP/MSTP( Rapid Spanning Tree Protocol) EPPS ring network protocol EAPS ring network protocol
Port characteristics	10 / 100 / 1000baset (x) automatic detection, full / half duplex MDI / mdi-x adaptive
Bandwidth	128Gbps （No blocking）
Packet Forwarding	40.32Mpps
MAC	8K
Buffer	4.1M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(=250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximumdistance =120km (depending on the optical module)
FLASH	16M
RAM	128M
Overall power consumption	≤30W
Forwarding mode	Store and forward (full line speed)
LED Indicator	V1:main power indicator V2:slave power indicator 17 18:(optical port connection indicator) Port: (network connection indicator green / 100M + Orange / 1000M)
Supporting power supply	Built in AC： 100~240V 50/60HZ
Storage Temperature/ Humidity	-40~+80°C;10%~90% RH No coagulation
Operating Temperature/ Humidity	-40~+85°C;5%~95% RHR No coagulation
Product size/Packing size(L*W*H)	295mm*195mm*45mm 410mm*275mm*95mm
N.W/G.W(kg)	1.4kg/2.1kg
Installation	DIN rail type (another wall mounting lug)
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.