

Model	G500-5G
Product name	5-port full 1000Mbps industrial grade switch
Fixed Port	4*10/100/1000M RJ45 port 1*1000M Uplink RJ45 port
Bandwidth	10Gbps
Packet Forwarding	7.44Mpps
MAC	2K
Buffer	2.5M
Transmission Distance	10 Mbps: Cat3,4,5 UTP (≦ 250 meters) 100 Mbps: Cat5 or later UTP (150 meters) 1000 Mbps: Cat6 or later UTP (150 meters)
LED Indicator	PW: Power indicator light (green) Port: Green_10/100M network connection indicator light Green +Orange_1000M network connection indicator light V1: Main power indicator light (green) V2: From power indicator light (green)
Watt	3 independent power inputs SW: DC 12-57V
Operating Temperature/Humidity	-40~+80°C; 10%~90% RH No coagulation
Storage Temperature/Humidity	-40~+85°C; 5%~95% RH No coagulation
Lightning Protection Level	6KV 8/20us; 8KV ESD IP40
Product Size/ Packing Size (L*W*H)	105mm*90mm*36mm 200mm*130mm*40mm
N.W/G.W(kg)	0.5kg/0.6kg
Installation	DIN guide rail type(additional wall hangers)
Certificate	3C; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.