

Hardware specifications

Model	G500P-5G
Model Product name	
Product name	5-port full 1000Mbps industrial grade PoE switch
Fixed Port	4 * 10/100/1000M RJ45 PoE port 1 * 10/100/1000M RJ45 uplink network port
PoE port	1 port supports IEEE802.3af/at/poe++/bt, with a maximum power of 90W 2-4 ports support IEEE802.3af/at, with a maximum of 30W/port
PoE power supply polarity	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
Bandwidth	10Gbps
Packet Forwarding	7.44Mpps
MAC	2K
Buffer	2.5M
Transmission Distance	10 Mbps: Cat3,4,5 UTP (≤ 250 meters) 100 Mbps: Cat5 or later UTP (150 meters) 1000 Mbps: Cat6 or later UTP (150 meters)
LED Indicator	PW: Power indicator light (green) Uplink port: green 100M+orange 1000M PoE port: Orange PoE indicator light, green network connection indicator light V1: Main power indicator light (green) V2: From power indicator light (green)
Watt	3 independent power inputs POE: DC 37-57V
Operating Temperature/Humidity	, -40~+80°C; 10%~90% RH No coagulation
Storage Temperature/Humidity	, -40~+85°C; 5%~95% RH No coagulation
Lightning Protection Level	6KV 8/20us; 8KV ESD IP40
Product Size/ Packing Size (L*W*H)	105mm*90mm*36mm 200mm*130mm*40mm
N.W/G.W(kg)	0.5kg/0.6kg
Installation	DIN guide rail type(additional wall hangers)
Certificate	3C; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes