

<div><div>hasivo®</div><div>Hardware specifications</div></div>	
Model	S1100P-4G-2S-Ai
Product name	Full Gigabit 4+2 PoE Switch
Fixed Port	4*10/100/1000Base-TX PoE port (Data/Power) 2*1000M SFP
PoE Ports	1-4 port supports PoE(first port outputs HiPoE_60W)
Function	N:(Standard normal) V:(Port isolation) S:(Ultral-far mode) (specific port refers to user manual) Ai version:PoE auto execution、detection and resets fault device, when PoE is on.
Network protocol	IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x IEEE 802.3af/at/PoE++ hasivo HiPoE
PoE Standard	IEEE802.3af/at/PoE++/HiPoE
Bandwidth	16Gbps
Packet Forwarding	14.44Mpps
MAC	2K
Buffer	2.5M
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter)
Power Pin	Default 1/2(+), 3/6(-); Optional order 4/5(+), 7/8(-)
Single port power	Average 15.4W；MAX 30W
Total power/ Input voltage	MAX 80W (AC100-240V 50/60HZ)
Watt	Standby Power Consumption：≤8W
LED Indicator	P:Power LED (Over-power LED) Uplink: (Link LED=10/100M Link) Port: (Orange=PoE LED+Green=Link LED) V:(Port Isolation LED) S:(Ultral-far Mode LED)
Supporting power supply	Built-in Power AC：100～240V 50-60Hz 1A
Storage Temperature/ Humidity	-10～+55℃；5%～90% RH Non coagulation
Operating Temperature/ Humidity	-40～+75℃；5%～95% RH Non coagulation
Product size/Packing size(L*W*H)	210mm*150mm*35mm 270*mm220mm*68mm
N.W/G.W(kg)	0.7kg/1.1kg
Installation	Desktop (optional wall hanger parts)
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.