

| | |
|---|---|
| <div><div>hasivo®</div><div>Hardware specifications</div></div> | |
| Model | S600P-4G-2G-Ai |
| Product name | 4Port Fast Ethernet PoE Switch |
| Fixed Port | 4*10/1000Base-TX PoE port （Data/Power） 2*10/1000Base-TX uplink RJ45 port(Data) |
| PoE Ports | 1-4 port supports PoE(first port outputs HiPoE_60W) |
| Function | N:(Standard normal) V:(Port isolation) S:(Ultral-far mode) （specific port refers to user manual） Ai version:PoE auto execution、 detection and resets fault device, when PoE is on. |
| Network protocol | IEEE 802.3 IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x IEEE 802.3af/at/PoE++ hasivo HiPoE |
| PoE Standard | IEEE802.3af/at/PoE++/HiPoE |
| Bandwidth | 1.6Gbps |
| Packet Forwarding | 1.15Mpps |
| MAC | 1K |
| Buffer | 768K |
| Transmission Distance | 10BASE-T ： Cat3,4,5 UTP(≦250 meter) 100BASE-TX ： Cat5 or later UTP(150 meter) |
| Power Pin | Default 1/2(+), 3/6(-); Optional order 4/5(+), 7/8(-) |
| Single port power | 15.4W/30W (first port MAX 60W) |
| Total power/ Input voltage | MAX 65W （AC100-240V） |
| Watt | Standby Power Consumption： <3W; Full-load Power Consumption： <65W |
| LED Indicator | P:Power LED （Over-power LED） Uplink: （Link LED=10/100M Link） Port: （Orange=PoE LED+Green=Link LED） V:(Port Isolation LED) S:(Ultral-far Mode LED) |
| Supporting power supply | Built-in Power AC： 100～240V 50-60Hz 1A |
| Storage Temperature/ Humidity | -10～+55℃； 5%～90% RH Non coagulation |
| Operating Temperature/ Humidity | -40～+75℃； 5%～95% RH Non coagulation |
| Product size/Packing size(L*W*H) | 190mm*130mm*35mm 305mm*205mm*55mm |
| N.W/G.W(kg) | 0.6kg/0.9kg |
| Installation | Desktop (optional wall hanger parts) |
| Warranty | Whole device for 1 year(Accessories not included) |

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.