

Model	F1200W-9S-2G
Product	Full Gigabit 9SFP+2GE L2+ Optical Convergence Managed Switch
Fixed Port	9*1000M SFP 2*10/100/1000Base-TX uplink RJ45 port(Data)
Console port	1*console port
Reset Key	1
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	56G/128Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) SFP: 100M/1G/10G single-mode multi-mode optical module, the maximum distance is ≤120km (depending on the optical module)
LED Indicator	PWR:Power LED SYS:System LED 1-2:10/100、1000M Network connection indicator 3-11:SFP connection indicator
Power	External power supply: DC: 12V 2A, max 24W (100-240Vac 50/60Hz 0.3A)
Operating Temperature/Humidity	-10~+55℃；5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃；5%~95% RH Non coagulation
Product /Packing size(L*W*H)	245mm*108mm*40mm 298mm*205mm*56mm
N.W/G.W(kg)	0.7kg/1.1kg
Lightning Protection level	6KV 8/20us；IP30
Installation	Desktop
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)