

Model	F1300W-8S-4S+_RTL
Product	10G Uplink 4SFP+8SFP L3 Managed Switch
Fixed Port	8*100/1000M SFP 4*100/1000/2500/10000M SFP
Console port	1*console port
Reset Key	1
CPU	MIPS-34Kc 800GHz
DDR	4G DDR3
FLASH	512MBytes
RAM	512MBytes
Bandwidth	256Gbps
Packet Forwarding	95.23Mpps
MAC	16K
Buffer	12Mbit SRAM Packet Buffer
Jumbo Frame	Jumbo frame up to 12KB
VLAN Address	4K
Link Aggregation	Supports 128 trunk groups with up to 8 members per group
L3 Routing	IPV4 supports 6K; IPV6 supports 2K;
QoS Queue	8
Transmission Distance	10BASE-T ： Cat3,4,5 UTP(≤250 meter) 100BASE-TX ： Cat5 or later UTP(150 meter) 1000BASE-TX ： Cat6 or later UTP(150 meter) SFP: 100M/1G/10G single-mode multi-mode optical module, the maximum distance is ≤120km (depending on the optical module)
LED Indicator	PWR:Power LED SYS:System LED 1-8:100、 1000M SFP connection indicator 9-12:10G SFP connection indicator
Power	Built-in power AC:100-240Vac 50-60Hz 0.3A max 25W
Operating Temperature/Humidity	-10~+55℃； 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃； 5%~95% RH Non coagulation
Product /Packing size(L*W*H)	333mm*195mm*45mm 410mm*278mm*95mm
N.W/G.W(kg)	1.8kg/2.5kg
Lightning Protection level	6KV 8/20us； IP30
Installation	Rack-mount(optional machine hanger spare parts)
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)

