

Model	F5800W-18S-8G
Product	Full Gigabit 18SFP+8GE L2+ Optical Convergence Managed Switch
Fixed Port	18*1000M SFP 8*10/100/1000Base-TX uplink RJ45 port(Data)
Console port	1*console port
Reset Key	1
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	56G/128Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) SFP: 100M/1G/10G single-mode multi-mode optical module, the maximum distance is ≤120km (depending on the optical module)
LED Indicator	PWR:Power LED SYS:System LED 1-8:10/100、1000M Network connection indicator 9-26:SFP connection indicator MS:Master power LED SL:Slave power LED
Power	Built-in power AC：Redundant dual power supplies 100-240Vac 50-60Hz 0.5A max 35W
Operating Temperature/Humidity	-10～+55℃；5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃；5%～95% RH Non coagulation
Product /Packing size(L*W*H)	440mm*200mm*45mm 515mm*300mm*95mm
N.W/G.W(kg)	2.5kg/3.3kg
Lightning Protection level	6KV 8/20us；IP30
Installation	Rack-mount(optional machine hanger spare parts)
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)