

Model	S1100W-8G-2S
Product	Full Gigabit 2SFP+8GE L2+ Managed Switch
Fixed Port	8*10/100/1000Base-TX uplink RJ45 port(Data) 2*1000M SFP
Console port	1*console port
Reset Key	1
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	20Gbps
Packet Forwarding	14.88Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) SFP: 100M/1G/10G single-mode multi-mode optical module, the maximum distance is ≤120km (depending on the optical module)
LED Indicator	POWER:Power LED 9-10:SFP connection indicator Port:Network connection indicator Green LED/100M +Orange LED/1000M
Power	External power DC：12V 1A max 12W (100-240Vac 50/60Hz 0.1A)
Operating Temperature/Humidity	-10～+55℃；5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃；5%～95% RH Non coagulation
Product /Packing size(L*W*H)	225mm*105mm*35mm 265mm*220mm*68mm
N.W/G.W(kg)	0.6kg/0.8kg
Lightning Protection level	6KV 8/20us；IP30
Installation	Desktop
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)