

Model	S1100WP-8G-2S
Product	Full Gigabit 2SFP+8GE L2+ Managed PoE Switch
Fixed Port	8*10/100/1000Base-TX PoE port(Data/Power) 2*1000M SFP
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 2-8 port supports IEEE802.3af/at, max 30W/port, PoE out
Console port	1*console port
Reset Key	1
PoE Pin	Af/at/bt: 12+ 45+ ; 36- 78- Af/at: 12+ 36-
PoE Bridge	Max 120W
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	20Gbps
Packet Forwarding	14.88Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10BASE-T ： Cat3,4,5 UTP(≤250 meter) 100BASE-TX ： Cat5 or later UTP(150 meter) 1000BASE-TX ： Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	POWER:Power LED 9-10:SFP connection indicator Uplink :Green LED=10/100M Link、 Orange=Gigabit Link Port:Orange=PoE LED, Green=LAN Link LED
Power	External power DC： 52V 2.5A max 130W (100-240Vac 50/60Hz 1.6A)
Operating Temperature/Humidity	-10～+55℃； 5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃； 5%～95% RH Non coagulation
Product /Packing size(L*W*H)	225mm*105mm*35mm 265mm*220mm*68mm
N.W/G.W(kg)	0.6kg/1.4kg
Lightning Protection level	6KV 8/20us； IP30
Installation	Desktop
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)