

Model	S1300WP-8XGT-SE
Product name	10 Gigabit WEB Managed PoE Switch
Fixed Port	8*100Mbps/1G/2.5G/5G/10Gbps RJ45 PoE 1*Reset Port
Port characteristics	10 / 100 / 1000baset (x) automatic detection, full / half duplex MDI / mdi-x adaptive
PoE Port	1 port: IEEE802.3af/at/bt (HiPoE) Max 90W 2-8 ports: IEEE802.3af/at Max 30W
CPU	800MHz MIPS-34Kc CPU
Bandwidth	160Gbps
Packet Forwarding	119.04Mpps
MAC	16K
Network protocol	IEEE802.3、IEEE802.3u、IEEE802.3ab、IEEE802.3z、IEEE802.3x
Total power	180W/300W
Transmission Distance	10BASE-T: unshielded twisted pair cables for categories 3, 4, and 5 (≤ 250 meters) 100BASE-T: unshielded twisted pair cable (100 meters) for Class 5 and above 1000BASE-T: unshielded twisted pair cable (100 meters) for Class 5 and above 2500BASE-T: unshielded twisted pair cable (100 meters) for Class 5 and above 10000BASE-T: unshielded twisted pair cable (30 meters) for Class 5 and above
LED Indicator	PWR: Power indicator (Green) SYS:System indicator (Green) RJ45 Left:10G Link/Act indicator (Orange) 5G Link/Act indicator (Green) RJ45 Right:2.5G Link/Act indicator (Orange) Link/Act indicator (Green) PoE:PoE Power indicator (Orange)
No-load power	≤14W
Power input	100-240Vac 50/60Hz 3.6A
Operating Temperature /Humidity	0℃~40℃; 10%~90% RH No condensation
Storage Temperature /Humidity	-40~+75℃; 5%~90% RH No condensation
size	Product :333mm*195mm*45mm Packing :410mm*278mm*95mm
N.W/G.W (kg)	2.32kg/2.92kg
Installation	Desktop/Rack mounted
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.