

Model	S2600W-8G-4TC
Product	Full Gigabit 4SFP+12GE L2+ Managed Switch
Fixed Port	8*10/100/1000Base-TX uplink RJ45 port (Data) 4*10/100/1000M RJ45(COMBO) 4*100/1000M SFP(COMBO)
Console port	1*console port
Reset Key	1
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	56G/128Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) SFP: 100M/1G/10G single-mode multi-mode optical module, the maximum distance is ≤120km (depending on the optical module)
LED Indicator	POWER:Power LED SYS:System LED 9-10:SFP connection indicator Port:Network connection indicator Green LED/100M +Orange LED/1000M
Power	Built-in power AC：100-240Vac 50-60Hz 0.2A max 15W
Operating Temperature/Humidity	-10～+55℃；5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃；5%～95% RH Non coagulation
Product /Packing size(L*W*H)	293mm*190mm*45mm 410mm*278mm*95mm
N.W/G.W(kg)	1.3kg/2.0kg
Lightning Protection level	6KV 8/20us；IP30
Installation	Desktop(optional machine hanger spare parts)
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)