

Model	S2800W-24G-2TS-SE
Product name	Built in 26GE-2SSFP Gigabit Smart Web switch
Fixed Port	24* 10/100/10000base TX RJ45 ports(data) 24* 10/100/10000base TX RJ45 ports(data) 2 x 1000m SFP 1 reset* restore factory configuration button
Port characteristics	10 / 100 / 1000baset (x) automatic detection, full / half duplex MDI / mdi-x adaptive
Bandwidth	56Gbps (No blocking)
Packet Forwarding	40.32Mpps
MAC	8K
Network protocol	IEEE 802.3,802.3i,802.3u,802.3x,802.3ab,802.3z
Buffer	4M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
LED Indicator	Power: power indicator 25-26 ports: (100M / 1000m prompt light green) 1-24 ports: (100M / 1000m prompt light green)
Overall power consumption	Full load maximum 25W
Power	Built in AC: 100~240V 50-60Hz 0.4A
Operating Temperature /Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75℃; 5%~95% RH Non coagulation
size	Product :440mm*140mm*45mm Packing :513mm*220mm*95mm
N.W/G.W (kg)	1.8kg/2.4kg
Installation	Desktop (optional with wall mounted and rack mounted ear accessories)
Certificate	3C; CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.