

Model	S2800WP-16G-2S-SE
Product name	Built in 16GE-2SSFP Gigabit Smart Web Poe switch
Fixed Port	16* 10/100/10000base TX Poe ports(data/power) 2 x 1000m SFP 1 reset* restore factory configuration button
Port characteristics	10 / 100 / 1000baset (x) automatic detection, full / half duplex MDI / mdi-x adaptive
PoE Port	Port 1-2: support ieee803.2af/at/poe + + / BT, max power 90W 3-16 ports: support ieee803.2af/at, single port, max power 30W 1-16 ports support PoeDog Function
PoE pin	1-2port: 1245+ 3678- 3-16ports: 12+ 36-
Bandwidth	56Gbps (No blocking)
Packet Forwarding	40.32Mpps
MAC	8K
Network protocol	IEEE 802.3,802.3i,802.3u,802.3x,802.3ab,802.3z IEEE 802.3af/at/POE++/BT
Poe total power	≤ 240W
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
LED Indicator	Power: power indicator 7-18 ports: (100M / 1000m prompt light green) 1-16 ports: (100M / 1000m prompt light green) Port 1-16 POE: Poe on light orange
Overall power consumption	Full load maximum 260W
Power	Built in AC: 100~240V 50-60Hz 4A
Operating Temperature /Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75℃; 5%~95% RH Non coagulation
size	Product :440mm*220mm*45mm Packing :515mm*375mm*95mm
N.W/G.W (kg)	3.0kg/3.6kg
Installation	Desktop (optional with wall mounted and rack mounted ear accessories)
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.