

Model	S5800WP-24G-4TC-BT
Product	Full Gigabit 4SFP+28GE BT L2+ Managed PoE Switch
Fixed Port	24*10/100/1000Base-TX PoE port(Data/Power) 4*10/100/1000M RJ45(COMBO) 4*100/1000M SFP(COMBO)
PoE Ports	1-24 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out
Console port	1*console port
Reset Key	1
PoE Pin	Af/at/bt: 12+ 45+ ; 36- 78-
PoE Bridge	Max 800W
CPU	500MHz
DDR	1G DDR3
FLASH	128MBytes
RAM	128MBytes
Bandwidth	56G/128Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1 Mbit SRAM Packet Buffer
Jumbo Frame	10000Bytes
VLAN Address	4K
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	PWR:Power LED SYS:System LED 1-24:10/100、 1000M Network connection indicator 25-28:10/100、 1000M Network connection indicator
Power	Built-in power AC： 100-240Vac 50-60Hz 9.9A max 825W
Operating Temperature/Humidity	-10～+55℃； 5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃； 5%～95% RH Non coagulation
Product /Packing size(L*W*H)	440mm*290mm*45mm 515mm*375mm*95mm
N.W/G.W(kg)	3.9kg/4.8kg
Lightning Protection level	6KV 8/20us； IP30
Installation	Rack-mount(optional machine hanger spare parts)
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)