



Hardware specifications

Model	S600W-4GT-2XGT-SE
Product name	WEB managed switch
Fixed Port	4个10/100/1000/2500Mbps RJ45 Port 2个10G/5G/2.5G/1G/1000M/100Mbps RJ45 port
performance	store and forward
Bandwidth	60Gbps
Packet Forwarding	44.64Mpps
Network standards	IEEE802.3、IEEE802.3u、IEEE802.3ab、IEEE802.3z、IEEE802.3x
Dip switch	DUMB:Non-management mode，this mode, you cannot access the WEB WEB：Management mode，this mode can be accessed by WEB
Network port characteristics	10/100/1000/2500/10000BaseT （X）Automatic detection，full/half duplex MDI/MDI-X adaptive
Forwarding mode	store and forward （full line speed）
Transmission Distance	10BASE-T:Cat3,4,5 UTP(≤250 meter) 100BASE-T:Cat5 or later UTP(100 meter) 1000BASE-T:Cat5 or later UTP(100 meter) 2500BASE-T:Cat5 or later UTP(100 meter) 10000BASE-T:Cat5 or later UTP(50 meter)
LED Indicator	PWR:Power indicator/System Signal indicator (green) 2.5G RJ45 left:2.5G link LED (yellow) 1G link LED (green) 2.5G RJ45 right:link LED/Signal Transmission indicator (green) 10G RJ45 left:10G link LED (yellow) 5G/2.5G link LED (green) 10G RJ45 right:link LED/Signal Transmission indicator (green)
No-load power consumption	≤3W
Product size/Packing size （L*W*H）	160mm*113mm*31mm 270mm*219mm*67mm
Input method	DC 12V （connector 5.5*2.1mm ）
Matching power supply	DC （12V1.5A）
Usage environment	operation temperature :0℃～40℃ storage temperature :-40℃～75℃ Working humidity :10%～90%, RH Non coagulation Storage Humidity :5%～90%, RH Non coagulation
N.W/G.W （kg）	2.2kg/3.1kg
Installation	Desktop
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.