

Model	S600WP-5GT-1SX-SE
Product name	10G Uplink Smart WEB Managed PoE Switch
Fixed Port	5*10/100/1000/2500Base-TX uplink RJ45 port (Data+Power) 1*1000/2.5G/10G SFP+ (Data)
PoE Ports	1 port supports IEEE802.3af/at/bt, max 90W/port PoE out 2-4 port supports IEEE802.3af/at, max 30W/port, PoE out
Bandwidth	35Gbps
Packet Forwarding	33.48Mpps
Buffer	8.1 Mbit SRAM Packet Buffer
PoE Pin	Af/at/bt: 12+ 45+ ; 36- 78- Af/at: 12+ 36-
PoE Bridge	max 65W
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(≤150 meter) 1000BASE-TX : Cat6 or later UTP(≤150 meter) 2500BASE-TX : Cat6 or later UTP(≤100 meter)
LED Indicator	PWR:Power LED/SYS LED 1-5 Ports: Link/Act LED、1G speed LED、2.5G speed LED Port 6: Link/Act LED POE: POE on LED
Power	External power DC: 52V1.25A max 65W (100-240Vac 50/60Hz 0.9A)
Operating Temperature /Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature /Humidity	-40~+75°C; 5%~95% RH Non coagulation
size	Product :160mm*112mm*30mm Packing:265mm*220mm*68mm
N.W/G.W (kg)	0.55kg/1.1kg
Installation	Desktop
Certificate	3C; CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.