

Model	S1100P-4G-2S
Product	Full Gigabit 2SFP+4GE POE Switch
Fixed Port	4*10/100/1000Base-TX PoE port(Data/Power) 2*1000M SFP
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 2-4 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Dog	Support PoE auto execution、 detection and resets fault device,when PoE is on
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 65W
Bandwidth	16Gbps
Packet Forwarding	8.93Mpps
MAC	2K
Buffer	2.5M
Transmission Distance	10BASE-T： Cat3,4,5 UTP(≤250 meter) 100BASE-TX： Cat5 or later UTP(150 meter) 1000BASE-TX： Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	P:Power LED(over-power LED) Uplink:(Link LED=10/100M Link、 1000M=Gigabit Link) Port:(Orange=PoE LED, Green=LAN Link LED) V:(Port isolation LED) S:(Super mode LED)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC： 100-240Vac 50-60Hz 0.9A max 68W
Operating Temperature/Humidity	-10～+55℃； 5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃； 5%～95% RH Non coagulation
Product /Packing size(L*W*H)	210mm*150mm*35mm 265mm*220mm*68mm
N.W/G.W(kg)	0.8kg/1.1kg
Installation	Desktop(optional wall +machine hangers)
Lightning Protection level	6KV 8/20us； IP30
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)