

Model	S1100P-8F-2G
Product	Gigabit uplink 8-port POE switch
Fixed Port	8*10/100Base-TX PoE port(Data/Power) 2*10/100/1000Base-TX uplink RJ45 port(Data)
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 2-8 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Dog	Support PoE auto execution、 detection and resets fault device,when PoE is on
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 120W
Bandwidth	16Gbps
Packet Forwarding	4.17Mpps
MAC	2K
Buffer	4M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
LED Indicator	P:Power LED(over-power LED) Uplink:(Link LED=10/100M Link、 1000M=Gigabit Link) Port:(Orange=PoE LED, Green=LAN Link LED) V:(Port isolation LED) S:(Super mode LED)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC: 100-240Vac 50-60Hz 1.5A max 125W
Operating Temperature/Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃; 5%~95% RH Non coagulation
Product /Packing size(L*W*H)	210mm*150mm*35mm 265mm*220mm*68mm
N.W/G.W(kg)	0.8kg/1.2kg
Installation	Desktop(optional wall +machine hangers)
Lightning Protection level	6KV 8/20us; IP30
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

We will try our best to check the errors in printing and pictures,However, hasivo is not responsible for possible omissions.The appearance, specifications, parameters, prices and product supply of the products listed on this page are subject to change without notice.