

Model	S1200P-8G-1TS
Product	Full Gigabit 1SFP+9GE POE Switch
Fixed Port	8*10/100/1000Base-TX PoE port(Data/Power) 1*10/100/1000Base-TX uplink RJ45 port(Data) 1*1000M SFP
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 2-8 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Dog	Support PoE auto execution、 detection and resets fault device,when PoE is on
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 150W
Bandwidth	20Gbps
Packet Forwarding	14.88Mpps
MAC	4K
Buffer	2.5M
Transmission Distance	10BASE-T： Cat3,4,5 UTP(≤250 meter) 100BASE-TX： Cat5 or later UTP(150 meter) 1000BASE-TX： Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	P:Power LED(over-power LED) Uplink:(Link LED=10/100M Link、 1000M=Gigabit Link) Port:(Orange=PoE LED, Green=LAN Link LED) V:(Port isolation LED) S:( Super mode LED)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC： 100-240Vac 50-60Hz 1.9A max 155W
Operating Temperature/Humidity	-10~+55℃； 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃； 5%~95% RH Non coagulation
Product /Packing size(L*W*H)	206mm*140mm*45mm 265mm*220mm*68mm
N.W/G.W(kg)	1.0kg/1.4kg
Installation	Desktop(optional wall +machine hangers)
Lightning Protection level	6KV 8/20us； IP30
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)

We will try our best to check the errors in printing and pictures,However, hasivo is not responsible for possible omissions.The appearance, specifications, parameters, prices and product supply of the products listed on this page are subject to change without notice.