

Model	S1200P-8G-2G
Product	10 Port Full Gigabit PoE Switch
Fixed Port	8*10/100/1000Base-TX PoE port(Data/Power) 2*10/100/1000Base-TX uplink RJ45 port(Data)
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 2-8 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Dog	Support PoE auto execution、detection and resets fault device,when PoE is on
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 150W
Bandwidth	20Gbps
Packet Forwarding	14.88Mpps
MAC	2K
Buffer	2.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter)
LED Indicator	P:Power LED(over-power LED) Uplink:(Link LED=10/100M Link、1000M=Gigabit Link) Port:(Orange=PoE LED, Green=LAN Link LED) V:(Port isolation LED) S:( Super mode LED)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC: 100-240Vac 50-60Hz 1.9A max 155W
Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non coagulation
Product /Packing size(L*W*H)	206mm*140mm*45mm 265mm*220mm*68mm
N.W/G.W(kg)	1.2kg/1.6kg
Installation	Desktop(optional wall +machine hangers)
Lightning Protection level	6KV 8/20us; IP30
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

The data presented above represents the performance of the product in specific equipment and experimental environments. Based on the actual on-site environment or differences in equipment, there may be differences. The technical comparisons mentioned are based on scientific principles and do not involve other purposes

Due to real-time changes in product version, batch, and production supply factors, in order to provide as accurate product information and functional parameters as possible, Hasivo may adjust the content on the above pages in real time to ensure consistency with the actual product. Any adjustments are subject to no further notice. Due to factors such as measurement environment and method, there may be certain scientific errors in product dimensions, parameters, and other information.