

Model	S1200P-8G-2S-AUTO
Product	24V/48V automatic matching 2SFP+8GE full Gigabit POE Switch
Fixed Port	8*10/100/1000Base-TX PoE port(Data/Power) 2*1000M SFP
PoE Ports	8*24V/48V automatically identify the matching POE port 1-8 port support detection 24V power supply, max 30W/port 1-8 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Dog	Support PoE auto execution、 detection and resets fault device,when PoE is on
PoE Pin	48V: 12+ 36- 24V: 45+ 78
PoE Bridge	Max 150W
Bandwidth	20Gbps
Packet Forwarding	14.88Mpps
MAC	4K
Buffer	2.5M
Transmission Distance	10BASE-T : Cat3,4,5 UTP(≤250 meter) 100BASE-TX : Cat5 or later UTP(150 meter) 1000BASE-TX : Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	P:Power LED(over-power LED) 9-10:SFP connection indicator PoE:48V ON: orange light is always on; 24V ON: orange light flashes Link:10/100/1000M(green)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC: 100-240Vac 50-60Hz 1.9A max 158W
Operating Temperature/Humidity	-10~+55℃; 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃; 5%~95% RH Non coagulation
Product /Packing size(L*W*H)	206mm*140mm*45mm 265mm*220mm*68mm
N.W/G.W(kg)	1.1kg/1.3kg
Installation	Desktop(optional wall +machine hangers)
Lightning Protection level	6KV 8/20us; IP30
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS;
Warranty	Whole device for 1 year(Accessories not included)

We will try our best to check the errors in printing and pictures,However, hasivo is not responsible for possible omissions.The appearance, specifications, parameters, prices and product supply of the products listed on this page are subject to change without notice.