

Model	S2600P-16F-1G-1TC-300W
Product	Hybrid Gigabit uplink 16-port 100M POE switch
Fixed Port	16*10/100Base-TX PoE port(Data/Power) 1*10/100/1000Base-TX uplink RJ45 port(Data) 1*1000M COMBO
PoE Ports	1-2 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 3-16 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Dog	Support PoE auto execution、 detection and resets fault device,when PoE is on
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 300W
Bandwidth	20Gbps
Packet Forwarding	6.55Mpps
MAC	8K
Buffer	4M
Transmission Distance	10BASE-T： Cat3,4,5 UTP(≤250 meter) 100BASE-TX： Cat5 or later UTP(150 meter) 1000BASE-TX： Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	POWER:Power LED(over-power LED) 18:SFP connection indicator S:Super mode LED Uplink:(Link LED=10/100M Link、 1000M=Gigabit Link) Port:(Orange=PoE LED, Green=LAN Link LED)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC： 100-240Vac 50-60Hz 3.7A max 308W
Operating Temperature/Humidity	-10～+55℃； 5%～90% RH Non coagulation
Storage Temperature/Humidity	-40～+75℃； 5%～95% RH Non coagulation
Product /Packing size(L*W*H)	295mm*195mm*45mm 410mm*278mm*95mm
N.W/G.W(kg)	1.8kg/2.6kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning Protection level	6KV 8/20us； IP30
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)