

Model	S2600P-16G-2TS
Product	Full Gigabit 2SFP+18GE POE Switch
Fixed Port	16*10/100/1000Base-TX PoE port(Data/Power) 2*10/100/1000Base-TX uplink RJ45 port(Data) 2*1000M SFP
PoE Ports	1-2 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 3-16 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Dog	Support PoE auto execution、 detection and resets fault device,when PoE is on
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 150W
Bandwidth	56Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1M
Transmission Distance	10BASE-T： Cat3,4,5 UTP(≤250 meter) 100BASE-TX： Cat5 or later UTP(150 meter) 1000BASE-TX： Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	POWER:Power LED 19-20:SFP connection indicator Uplink:(10/100M=Green Link、 1000M=Orange Link) Downlink:(10/100M=Green Link、 1000M=Orange Link)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC： 100-240Vac 50-60Hz 2A max 165W
Operating Temperature/Humidity	-10~+55℃； 5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃； 5%~95% RH Non coagulation
Product /Packing size(L*W*H)	293mm*190mm*45mm 410mm*278mm*95mm
N.W/G.W(kg)	1.7kg/2.4kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning Protection level	6KV 8/20us； IP30
Certificate	CE-EMC EN55032； CE-LVD EN62368； FCC Part 15 Class B； RoHS；
Warranty	Whole device for 1 year(Accessories not included)

We will try our best to check the errors in printing and pictures,However, hasivo is not responsible for possible omissions.The appearance, specifications, parameters, prices and product supply of the products listed on this page are subject to change without notice.