



Hardware

Model	S500P-2G-1S
Product	Full Gigabit 1SFP+2GE POE Switch
Fixed Port	2*10/100/1000Base-TX PoE port(Data/Power) 1*1000M SFP
PoE Ports	1-2 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Pin	12+ 36-
PoE Bridge	Max 30W
Bandwidth	12Gbps
Packet Forwarding	4.46Mpps
MAC	2K
Buffer	2.5M
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter)
LED Indicator	POWER:Power LED(over-power LED) Uplink3:SFP LED Port:(Orange=PoE LED, Green=LAN Link LED)
Power	External power DC：52V 600MA max 31W (100-240Vac 50/60Hz 0.4A)
Operating Temperature/Humidity	-10~+55℃；5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃；5%~95% RH Non coagulation
Product /Packing size(L*W*H)	90mm*85mm*27mm 205mm*135mm*95mm
N.W/G.W(kg)	0.2kg/0.8kg
Installation	Desktop
Lightning Protection level	6KV 8/20us；IP30
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS
Warranty	Whole device for 1 year(Accessories not included)

We will try our best to check the errors in printing and pictures,However, hasivo is not responsible for possible omissions.The appearance, specifications, parameters, prices and product supply of the products listed on this page are subject to change without notice.