

Model	S5800P-16G-2S
Product	Full Gigabit 2SFP+16GE POE Switch
Fixed Port	16*10/100/1000Base-TX PoE port(Data/Power) 2*1000M SFP
PoE Ports	1-2 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 3-16 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 300W
Bandwidth	56Gbps
Packet Forwarding	41.67Mpps
MAC	8K
Buffer	4.1M
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	PWR:Power LED(green) 1-16:10/100、1000M Network connection indicator(green) 17-18:SFP connection indicator(green) PoE:PoE indicator(orange)
Function	N:(Standard normal) V:(Port isolation) C:(Flow control mode)
Power	Built-in power AC：100-240Vac 50-60Hz 2A max 315W
Operating Temperature/Humidity	-10~+55℃；5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃；5%~95% RH Non coagulation
Product /Packing size(L*W*H)	440mm*290mm*45mm 515mm*375mm*95mm
N.W/G.W(kg)	3.3kg/4.0kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning Protection level	6KV 8/20us；IP30
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)