

Model	S5800P-24F-2TC
Product	Hybrid Gigabit uplink 24-port 100M POE switch
Fixed Port	24*10/100Base-TX PoE port(Data/Power) 2*1000M COMBO
PoE Ports	1-2 port supports IEEE802.3af/at/poe++/bt, max 90W PoE out 3-24 port supports IEEE802.3af/at, max 30W/port, PoE out
PoE Pin	af/at: 12+ 36- af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Bridge	Max 400W
Bandwidth	16Gbps
Packet Forwarding	6.55Mpps
MAC	4K
Buffer	4.1M
Transmission Distance	10BASE-T：Cat3,4,5 UTP(≤250 meter) 100BASE-TX：Cat5 or later UTP(150 meter) 1000BASE-TX：Cat6 or later UTP(150 meter) SFP: 1000M single and multimode optical module with maximum distance ≤ 120km (depending on the optical module)
LED Indicator	PWR:Power LED(green) 1-24:10/100M Network connection indicator(green) 25-26:10/100、1000M Network connection indicator(green) PoE:PoE indicator(orange)
Function	N:(Standard normal) V:(Port isolation) S:(Super mode)(specific port refers to user manual)
Power	Built-in power AC：100-240Vac 50-60Hz 5A max 410W
Operating Temperature/Humidity	-10~+55℃；5%~90% RH Non coagulation
Storage Temperature/Humidity	-40~+75℃；5%~95% RH Non coagulation
Product /Packing size(L*W*H)	440mm*290mm*45mm 515mm*375mm*95mm
N.W/G.W(kg)	3.4kg/4.1kg
Installation	Rack-mount(optional machine hanger spare parts)
Lightning Protection level	6KV 8/20us；IP30
Certificate	CE-EMC EN55032；CE-LVD EN62368； FCC Part 15 Class B；RoHS；
Warranty	Whole device for 1 year(Accessories not included)

We will try our best to check the errors in printing and pictures,However, hasivo is not responsible for possible omissions.The appearance, specifications, parameters, prices and product supply of the products listed on this page are subject to change without notice.